

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 889660



GEHÄUSE					ABTRIEBSRITZEL					MOTORFLANSCH				
Sollwert			Istwert		Sollwert			Istwert		Sollwert			Istwert	
			D7233					Q148						
	E1	355j6 ^{+0,018} _{-0,018}	µm	354,995	Zahnweite (über 3 Zähne)					Ø	B	181	µm	181
	E2	355j6 ^{+0,018} _{-0,018}	µm	354,982		G1	62,97 ⁰ _{-0,05}	Cmm	62,95	Ø	C	38 ^{+0,05} _{+0,025}	µm	38,03
n x H on PCD J	12 Ø17,5 on PCD 385	Cr	OK		↗	g1	0,03	Di	0,015		D	8	Cr	8
		Cr					Ø	S1	215	Cr	215			
	A	384,5	µm	384,96	Leerlaufdrehmoment					Ø	Y1	M12	Pg	OK
	L	178	µm	178,08	Linie 1			0,8 Nm						

				Geräuschpegel	
		Linie	Steifigkeit	@1000 rpm Eintrieb (dB(A))	62,0
	Verdrehsteifigkeit (Nm/arcmin)	1	1076,47		
	Radiale Steifigkeit (N/μm)	1	1201		

A stylized handwritten signature in black ink, possibly reading "J.P.", written over a horizontal orange and white plaid pattern.