

ANSCHLÜSSE & AUSSENABMESSUNGEN:		SN:	897098
--	--	------------	---------------



GEHÄUSE					GEHÄUSE					MOTORFLANSCH						
Sollwert					Istwert					Sollwert					Istwert	
					L1120											
	E	720 ⁰ _{-0,15}	Cmm	719,975		O1	50	Cr	50		Ø	B1	181	µm	181,039	
	G	920 ^{+0,3} _{-0,3}	Cmm	920,171		P11	105	Cr	105		Ø	C1	38 ^{+0,05} _{+0,025}	µm	38,05	
//	g	0,055	Cmm	0,036		P12	105	Cr	105			D1	8	Cr	8,465	
//	t	0,055	Cmm	0,002		M	320 ^{+0,1} _{-0,1}	Cmm	320,032		Ø	S1	215	Cr	215	
//	u	0,04	Cmm	0,004		O2	50	Cr	50		Ø	Y1	M12	Pg	M12	
//	v	0,055	Cmm	0,001		P21	105	Cr	105							
	W	180	Cmm	180,012		P22	105	Cr	105		Ø	B2	181	µm	181,035	
//	w	0,05	Cmm	0,001	ABTRIEBSRITZEL					Ø	C2	38 ^{+0,05} _{+0,025}	µm	38,05		
	X	180	Cmm	180	Zahnrad 1					Q2206			D2	8	Cr	8,539
//	x	0,05	Cmm	0,003	Zahnweite (über 3 Zähne)					Ø	S2	215	Cr	215		
	H	360 ^{+0,045} _{-0,045}	Cmm	360,013		G1	62,97 ⁰ _{-0,05}	Cmm	62,946		Ø	Y2	M12	Pg	M12	
//	h	0,03	Cmm	0,018		g1	0,03	Di	0,005			Linie	Steifigkeit			
	A1	452	Cmm	452,801	Zahnrad 2					Q0485		Verdrehsteifigkeit (Nm/arcmin)	1	1076		
	L1	157	Cmm	157,142	Zahnweite (über 3 Zähne)								2	1076		
	A2	452	Cmm	452,968		G2	62,97 ⁰ _{-0,05}	Cmm	62,895		Radiale Steifigkeit (N/µm)		1	1388		
	L2	157	Cmm	157,078		g2	0,03	Di	0,015			2	1414			
					Leerlaufdrehmoment					Geräuschpegel						
					Linie 1					2 Nm		@1000 rpm Eintrieb (dB(A))	69,5			
					Linie 2					2 Nm						

Datum: 12/06/2015

Version: A

ZZICONACCI *7/10/2024*

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr