

KRP

Ficha de resultado

RX183-006-A

1/2

CLIENTE:

AUTOPULIT

REF. PEDIDO:

58015 AUTOPULIT

DISTRIBUIDOR:

PEDIDO INTERNO:

210335

DESIGNACIÓN:

KRP2+R.31.4.H

NÚMERO DE SERIE:

898470

REFERENCIA :

RX128908-12

REFERENCIA DE LA BRIDA MOTOR:

RX129506-01

Para la instalación, por favor consulte el Manual de Usuario KRP (182/008)

OBSERVACIONES:

Las imágenes del producto son meramente ilustrativas.

REDEX

ANDANTEX

ZI-BP79  
F45210 FERRIERES  
www.redex.fr

Tel: +33 2 38 94 42 00  
Fax: +33 2 38 94 42 99  
Email: info@redex.fr

KRP

Ficha de resultado

RX183-006-A

2/2

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

898470

Technical drawing of the KRP2+R.31.4.H motor assembly. It includes a front view showing dimensions Q1, Q2, V, L, E1, and E2. A side view shows dimensions D, C, B, and S. A detail view shows 4 x Y on PCD S. A gear detail shows G1 and g1. The drawing also indicates n x H on PCD J.

|                         |     |                                                 |                                      |                  |        |                               |                               |                |                                     |            |        |
|-------------------------|-----|-------------------------------------------------|--------------------------------------|------------------|--------|-------------------------------|-------------------------------|----------------|-------------------------------------|------------|--------|
| General tolerance: Js13 | Cmm | Automatic / manual coordinate-measuring machine | µm                                   | Micrometer       | Cr     | Calliper rule                 | Di                            | Dial indicator | Pg                                  | Plug gauge |        |
| CARCASA                 |     |                                                 | PIÑÓN DE SALIDA                      |                  |        | BRIDA MOTOR                   |                               |                |                                     |            |        |
| requerida               |     |                                                 | real                                 |                  |        | requerida                     |                               |                | real                                |            |        |
|                         |     |                                                 | L2069                                |                  |        |                               |                               |                | P2264                               |            |        |
| E1                      |     |                                                 | 212h7 <sup>0</sup> <sub>-0,046</sub> | µm               | 211.97 | Medida cordal entre 4 dientes |                               |                | Ø B                                 |            |        |
| E2                      |     |                                                 | 200h7 <sup>0</sup> <sub>-0,046</sub> | µm               | 199.97 | G1                            |                               |                | 44,27 <sup>0</sup> <sub>-0,03</sub> | Cmm        | 44.25  |
| n x H on PCD J          |     |                                                 | 12 Ø9 on PCD 233                     | Cr               | OK     | g1                            |                               |                | 0,022                               | Di         | 0,015  |
| V                       |     |                                                 | 289                                  | µm               | 289.38 | Par entrada sin carga         |                               |                | Ø S1                                |            |        |
| L                       |     |                                                 | 94                                   | µm               | 93.84  | Línea 1                       |                               |                | 0,8 Nm                              |            |        |
| Ø Q1                    |     |                                                 | 25                                   | +0,009<br>-0,004 | µm     | 25                            | Rigidez torsional (Nm/arcmin) |                |                                     | 1          | 243,75 |
| Ø Q2                    |     |                                                 | 25                                   | +0,009<br>-0,004 | µm     | 25                            | Rigidez radial (N/µm)         |                |                                     | 1          | 528    |
|                         |     |                                                 |                                      |                  |        | Rigidez                       |                               |                | @2100 rpm entrada (dB(A))           |            |        |
|                         |     |                                                 |                                      |                  |        |                               |                               |                | 70,5                                |            |        |

Fecha:

11/02/2016

Revisado:

J ONGANER

Versión:

A

REDEX

ANDANTEX

ZI-BP79  
F45210 FERRIERES  
www.redex.fr

Tel: +33 2 38 94 42 00  
Fax: +33 2 38 94 42 99  
Email: info@redex.fr