

KRP

Ficha de resultado

RX183-006-A

Page

1/2

CLIENTE:

NICOLAS CORREA

REF. PEDIDO:

115119 NICOLAS CORREA

DISTRIBUIDOR:

PEDIDO INTERNO:

210399

DESIGNACIÓN:

KRP2+R.31.4.H

NÚMERO DE SERIE:

898526

REFERENCIA :

RX128908-12

REFERENCIA DE LA BRIDA MOTOR:

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

898526

Technical drawing of the KRP2+R.31.4.H unit. The drawing includes a front view, a side view, and a detail view of the output pinion. Dimensions are indicated as follows: Q1 and Q2 are diameters of the top flange; E1 and E2 are diameters of the main body; V and L are vertical dimensions; G1 and g1 are diameters of the output pinion; D, C, B, S, Y, J, H, and I are dimensions related to the motor flange and its mounting.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

µm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

PARA LA INSTALACIÓN, POR FAVOR CONSULTE EL MANUAL DE USUARIO KRP (182/008)

CARCASA				PIÑÓN DE SALIDA				BRIDA MOTOR							
requerida				real				requerida				real			
				L5056								-			
		E1	212h7 ⁰ _{-0,046}	µm	211.955		Medida cordal entre 4 dientes				Ø	B		µm	
		E2	200h7 ⁰ _{-0,046}	µm	199.95		G1 44,27 ⁰ _{-0,03} Cmm 44,26				Ø	C		µm	
		n x H on PCD J	12 Ø9 on PCD 233	Cr	OK		g1 0,022 Di 0,005					D		Cr	
		V	289	µm	289.37		Par entrada sin carga				Ø	S1		Cr	
		L	94	µm	93.83		Línea 1 0,6 Nm				Ø	Y1		Pg	
		Ø Q1	25 ^{+0,009} _{-0,004}	µm	25.009						Nivel sonoro				
		Ø Q2	25 ^{+0,009} _{-0,004}	µm	25.009						@2100 rpm entrada (dB(A)) 71,0				
							Rigidez torsional (Nm/arcmin) 1 243,75								
							Rigidez radial (N/µm) 1 452								

FECHA:

13/04/2016

REVISADO:

JJ PELLE

VERSIÓN:

A

Las imágenes del producto son meramente ilustrativas.

REDEX ANDANTEX

ZI-BP79 F45210 FERRIERES www.redex.fr

Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr

REDEX ANDANTEX

ZI-BP79 F45210 FERRIERES www.redex.fr

Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr