



BESONDERE ANMERKUNGEN:

GEHÄUSE					GEHÄUSE					MOTORFLANSCH											
Sollwert				Istwert		Sollwert				Istwert		Sollwert			Istwert						
				M2341																	
							L1	75	Cr	75											
	Y2	M8x15	Pg	OK			L2	70	Cr	70		Ø	B	181	µm	181					
Ø	S2	200 ^{+0,1 -0,1}	Cr	200			J	160	Cr	160		Ø	C	38 ^{+0,05 +0,025}	µm	8.52					
	A	399,5	µm	399.76			K	13	Cr	13			D	8	Cr	8.52					
	E	290	Cr	290		2 x 4Ø	Y4	M8x15	Pg	OK		Ø	S1	215	Cr	215					
	O	25	Cr	25			F1	50	Cr	50.38		Ø	Y1	M12	Pg	OK					
	P1	35	Cr	35			F2	25	Cr	24.7	Leerlaufdrehmoment										
	P2	35	Cr	35		2 x 1Ø	Y7	12	µm	12							Linie 1			1,5 Nm	
	P3	35	Cr	35		2 x 4Ø	Y6	17,5	µm	17.5											
	P4	35	Cr	35		2 x 5Ø	Y5	26	µm	26	Steifigkeit										
	T	17	Cr	17			M H6	12 ^{+0,011 0}	Cmm	12							Linie				
	U	32	Cr	32		⊥	m	0,05	Cmm	0,005							Verdrehsteifigkeit (Nm/arcmin)		1	473,03	
2 x 1Ø	Y3	M8x15	Pg	OK			N	71,5 ^{+0,1 -0,1}	Cmm	71,5	Radiale Steifigkeit (N/µm)		1	998							
	R	226 ^{+0,2 +0,1}	Cmm	226,134	A		W	135 ^{+0,035 -0,035}	Cmm	135,008											
⊙	r	0,1	Cmm	0,055		//	w	0,03	/A	Cmm	0										

Datum: 28/04/2016 Von: J ONGANER

Version: A