

KRP

Ficha de resultado

RX183-006-A

Page

1/2

CLIENTE:

LOXIN 2002 SL

REF. PEDIDO:

LCPE16-01495 LOXIN 2002

DISTRIBUIDOR:

PEDIDO INTERNO:

210613

DESIGNACIÓN:

KRP2+R.46.4.H

NÚMERO DE SERIE:

898884

REFERENCIA :

RX128908-13

REFERENCIA DE LA BRIDA MOTOR:

RX129506-02

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

898884

Technical drawing of the KRP2+R.46.4.H motor assembly. The drawing includes a front view, a side view, and a detail view of the output shaft. Dimensions are indicated as follows:
 - Front view: $\phi Q1$, $\phi Q2$, $\phi E1$, $\phi E2$, $n \times H$ on PCD J, $G1$, $g1$.
 - Side view: V , L .
 - Detail view: D , C , B , $4 \times Y$ on PCD S.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

μm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

PARA LA INSTALACIÓN, POR FAVOR CONSULTE EL MANUAL DE USUARIO KRP (182/008)

CARCASA					PIÑÓN DE SALIDA				BRIDA MOTOR								
requerida					real				requerida					real			
					M2511									P2279			
	E1	212h7 ⁰ _{-0,046}	μm	211.98	Medida cordal entre 4 dientes					ϕ	B	130 ^{+0,054} _{+0,014}	μm	/			
	E2	200h7 ⁰ _{-0,046}	μm	199.985		G1	44,27 ⁰ _{-0,03}	Cmm	44.25		ϕ	C	32 ^{+0,05} _{+0,025}	μm	/		
	$n \times H$ on PCD J	12 $\phi 9$ on PCD 233	Cr	OK		g1	0,022	Di	0,015		D	8	Cr	/			
	V	289	μm	289.46	Par entrada sin carga					ϕ	S1	165	Cr	/			
	L	94	μm	93.9	Línea 1				0,5 Nm			ϕ	Y1	M10	Pg	/	
	ϕ	Q1	25 ^{+0,009} _{-0,004}	μm	25.009					Nivel sonoro							
	ϕ	Q2	25 ^{+0,009} _{-0,004}	μm	25.009					@2100 rpm entrada (dB(A))				66,5			
					Rigidez torsional (Nm/arcmin)				1	243,75							
					Rigidez radial (N/ μm)				1	489							

OBSERVACIONES:

Fecha:

08/06/2016

Revisado:

J ONGANER

Versión:

A

Las imágenes del producto son meramente ilustrativas.

REDEX ANDANTEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

REDEX ANDANTEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr