

KRP

Ficha de resultado

RX183-006-A

1/2

CLIENTE:

LOXIN 2002 SL

REF. PEDIDO:

LCPE16-01495 LOXIN 2002

DISTRIBUIDOR:

PEDIDO INTERNO:

210613

DESIGNACIÓN:

KRP2+R.46.4.H

NÚMERO DE SERIE:

898885

REFERENCIA :

RX128908-13

REFERENCIA DE LA BRIDA MOTOR:

RX129506-02

Para la instalación, por favor consulte el Manual de Usuario KRP (182/008)

OBSERVACIONES:

Las imágenes del producto son meramente ilustrativas.

REDEX

ANDANTEX

ZI-BP79  
F45210 FERRIERES  
www.redex.fr

Tel: +33 2 38 94 42 00  
Fax: +33 2 38 94 42 99  
Email: info@redex.fr

KRP

Ficha de resultado

RX183-006-A

2/2

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

898885

Technical drawing of the KRP2+R.46.4.H motor assembly. The drawing includes a front view, a side view, and a detail view of the output shaft. Dimensions are indicated as follows:   
 - Front view:  $\phi Q1$ ,  $\phi Q2$ ,  $\phi E1$ ,  $\phi E2$ ,  $n \times H$  on PCD J,  $\phi G1$ ,  $g1$ .   
 - Side view:  $\phi C$ ,  $\phi B$ ,  $4 \times Y$  on PCD S.   
 - Detail view:  $\phi G1$ ,  $g1$ .

|                         |     |                                                 |                                        |            |        |                               |    |                |                                     |            |       |
|-------------------------|-----|-------------------------------------------------|----------------------------------------|------------|--------|-------------------------------|----|----------------|-------------------------------------|------------|-------|
| General tolerance: Js13 | Cmm | Automatic / manual coordinate-measuring machine | $\mu m$                                | Micrometer | Cr     | Calliper rule                 | Di | Dial indicator | Pg                                  | Plug gauge |       |
| CARCASA                 |     |                                                 | PIÑÓN DE SALIDA                        |            |        | BRIDA MOTOR                   |    |                |                                     |            |       |
| requerida               |     |                                                 | real                                   |            |        | requerida                     |    |                | real                                |            |       |
|                         |     |                                                 | M2505                                  |            |        |                               |    |                | O147                                |            |       |
| E1                      |     |                                                 | 212h7 <sup>0</sup> <sub>-0,046</sub>   | $\mu m$    | 211.97 | Medida cordal entre 4 dientes |    |                |                                     |            |       |
| E2                      |     |                                                 | 200h7 <sup>0</sup> <sub>-0,046</sub>   | $\mu m$    | 199.99 | G1                            |    |                | 44,27 <sup>0</sup> <sub>-0,03</sub> | Cmm        | 44.25 |
| n x H on PCD J          |     |                                                 | 12 $\phi 9$ on PCD 233                 | Cr         | OK     | g1                            |    |                | 0,022                               | Di         | 0,02  |
| V                       |     |                                                 | 289                                    | $\mu m$    | 289.47 | Par entrada sin carga         |    |                |                                     |            |       |
| L                       |     |                                                 | 94                                     | $\mu m$    | 93.67  | Línea 1                       |    |                | 0,5 Nm                              |            |       |
| $\phi Q1$               |     |                                                 | 25 <sup>+0,009</sup> <sub>-0,004</sub> | $\mu m$    | 25.009 |                               |    |                | Nivel sonoro                        |            |       |
| $\phi Q2$               |     |                                                 | 25 <sup>+0,009</sup> <sub>-0,004</sub> | $\mu m$    | 25.009 |                               |    |                | @2100 rpm entrada (dB(A))           |            |       |
|                         |     |                                                 |                                        |            |        | Rigidez torsional (Nm/arcmin) |    |                | 1                                   | 243,75     | 73,5  |
|                         |     |                                                 |                                        |            |        | Rigidez radial (N/ $\mu m$ )  |    |                | 1                                   | 482        |       |

Fecha:

07/06/2016

Revisado:

J ONGANER

Versión:

A

REDEX

ANDANTEX

ZI-BP79  
F45210 FERRIERES  
www.redex.fr

Tel: +33 2 38 94 42 00  
Fax: +33 2 38 94 42 99  
Email: info@redex.fr