

KRP

Ficha de resultado

RX183-006-A

Page

1/2

CLIENTE:

NICOLAS CORREA

REF. PEDIDO:

117334 NICOLAS CORREA

DISTRIBUIDOR:

PEDIDO INTERNO:

210760

DESIGNACIÓN:

KRP2+R.31.4.H

NÚMERO DE SERIE:

899085

REFERENCIA :

RX128908-12

REFERENCIA DE LA BRIDA MOTOR:

RX129627-01

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

899085

Technical drawing of the KRP2+R.31.4.H motor assembly. The drawing includes a front view, a side view, and a detail view of the output shaft. Dimensions are indicated as follows:
 - Front view: $\phi Q1$, $\phi Q2$, V , L , $\phi E1$, $n \times H$ on PCD J, $\phi E2$.
 - Side view: D , ϕC , ϕB , $4 \times Y$ on PCD S.
 - Detail view: $G1$, $g1$.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

μm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

Para la instalación, por favor consulte el Manual de Usuario KRP (182/008)

OBSERVACIONES:

CARCASA						PIÑÓN DE SALIDA				BRIDA MOTOR						
requerida			real			requerida		real		requerida			real			
			M1811					P2296								
	E1	212h7 ⁰ _{-0,046}	μm	211.99		Medida cordal entre 4 dientes				ϕ	B	180	^{+0,054} _{+0,014}	μm		
	E2	200h7 ⁰ _{-0,046}	μm	199.985		$\nearrow$	G1	44,27 ⁰ _{-0,03}	Cmm	44,26	ϕ	C	38	^{+0,05} _{+0,025}	μm	
n x H on PCD J		12 $\phi 9$ on PCD 233	Cr	OK		g1		0,022	Di	0,01		D	8		Cr	
V		289	μm	289.38		Par entrada sin carga				ϕ	S1	215		Cr		
L		94	μm	93.8		Línea 1				0,7 Nm		ϕ	Y1	M12	Pg	
ϕ	Q1	25	^{+0,009} _{-0,004}	μm	25.009					Nivel sonoro			@2100 rpm entrada (dB(A))			68,5
ϕ	Q2	25	^{+0,009} _{-0,004}	μm	25.009											
						Rigidez torsional (Nm/arcmin)		1	243,75							
						Rigidez radial (N/ μm)		1	528							

Fecha:

12/07/2016

Revisado:

J ONGANER

Versión:

A

Las imágenes del producto son meramente ilustrativas.

REDEX ANDANTEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

REDEX ANDANTEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr