

KRP

Ficha de resultado

RX183-006-A

1/2

CLIENTE:

NICOLAS CORREA

REF. PEDIDO:

117334 NICOLAS CORREA

DISTRIBUIDOR:

PEDIDO INTERNO:

210760

DESIGNACIÓN:

KRP2+R.31.4.H

NÚMERO DE SERIE:

899086

REFERENCIA :

RX128908-12

REFERENCIA DE LA BRIDA MOTOR:

RX129627-01

Page

2/2

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

899086

Technical drawing of the KRP2+R.31.4.H unit. The drawing includes a front view, a side view, and a detail view of the output gear. Dimensions are labeled as follows: Q1 and Q2 are diameters of the input shaft; V and L are vertical distances; E1 and E2 are diameters of the housing; G1 and g1 are diameters of the output gear; D, C, B, S, Y, J, and H are dimensions related to the motor flange and housing.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

μm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

PARA LA INSTALACIÓN, POR FAVOR CONSULTE EL MANUAL DE USUARIO KRP (182/008)

CARCASA					PIÑÓN DE SALIDA				BRIDA MOTOR										
requerida					real				requerida				real						
					M1810								P2310						
E1					212h7 ⁰ _{-0,046}	μm	211.98				Medida cordal entre 4 dientes				Ø B 180 ^{+0,054} _{+0,014} μm				
E2					200h7 ⁰ _{-0,046}	μm	199.98				G1				44,27 ⁰ _{-0,03} Cmm	44,25			
n x H on PCD J					12 Ø9 on PCD 233	Cr	OK				g1				0,022 Di	0,005			
V					289	μm	289.32				Par entrada sin carga				Ø S1 215 Cr				
L					94	μm	93.84				Línea 1				0,5 Nm				
Ø Q1					25 ^{+0,009} _{-0,004}	μm	25.005				Rigidez torsional (Nm/arcmin)				1	243,75			
Ø Q2					25 ^{+0,009} _{-0,004}	μm	25.005				Rigidez radial (N/μm)				1	537			

Fecha:

12/07/2016

Revisado:

J ONGANER

Versión:

A

Las imágenes del producto son meramente ilustrativas.

REDEX ANDANTEX

ZI-BP79 F45210 FERRIERES www.redex.fr

Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr

REDEX ANDANTEX

ZI-BP79 F45210 FERRIERES www.redex.fr

Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr