

KRP

Ficha de resultado

RX183-006-A

Page

1/2

CLIENTE:

NICOLAS CORREA

REF. PEDIDO:

DISTRIBUIDOR:

PEDIDO INTERNO:

210906

DESIGNACIÓN:

KRP2+R.31.4.H

NÚMERO DE SERIE:

899310

REFERENCIA :

RX128908-12

REFERENCIA DE LA BRIDA MOTOR:

RX129627-01

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

899310

Technical drawing of the KRP2+R.31.4.H unit. The drawing includes a front view, a side view, and a detail view of the output shaft. Dimensions are indicated as follows:
 - Front view: $\phi Q1$, $\phi Q2$, V , L , $\phi E1$, $n \times H$ on PCD J, $\phi E2$.
 - Side view: D , ϕC , ϕB .
 - Detail view: $4 \times Y$ on PCD S.
 - Output shaft: $G1$, $g1$.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

μm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

PARA LA INSTALACIÓN, POR FAVOR CONSULTE EL MANUAL DE USUARIO KRP (182/008)

CARCASA					PIÑÓN DE SALIDA				BRIDA MOTOR							
requerida					real				requerida				real			
					M5387								O989			
									Medida cordal entre 4 dientes							
					E1 212h7 ⁰ _{-0,046} μm 211.99								ϕ B 180 ^{+0,054} _{+0,014} μm 180.02			
					E2 200h7 ⁰ _{-0,046} μm 199.99								ϕ C 38 ^{+0,05} _{+0,025} μm 38.04			
					n x H on PCD J 12 ϕ 9 on PCD 233 Cr OK								ϕ D 8 Cr 8.1			
					V 289 μm 289.47								ϕ S1 215 Cr 215			
					L 94 μm 93.86								ϕ Y1 M12 Pg OK			
					ϕ Q1 25 ^{+0,009} _{-0,004} μm 25.009											
					ϕ Q2 25 ^{+0,009} _{-0,004} μm 25.009											
									Línea 1 0,5 Nm							
									Rigidez torsional (Nm/arcmin) 1 243,75				Nivel sonoro @2100 rpm entrada (dB(A)) 69,0			
									Rigidez radial (N/ μm) 1 497							

FECHA:

21/09/2016

REVISADO:

J ONGANER

VERSIÓN:

A

Las imágenes del producto son meramente ilustrativas.

REDEX ANDANTEX

ZI-BP79 F45210 FERRIERES www.redex.fr

Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr

REDEX ANDANTEX

ZI-BP79 F45210 FERRIERES www.redex.fr

Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr