

DRP				DRP				Page																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
Performance sheet				RX183/005-B				1/2																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
CUSTOMER: MHI				CUSTOMER ORDER REF: 161207IB-1 MHI				EXTERNAL DIMENSIONS & INTERFACES:																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
DISTRIBUTOR: S & F INC				REDEX ORDER REF: 211416				SN: 899872																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
DESIGNATION: DRP3+M.46.3.H.28/38				SERIAL NUMBER: 899872																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
CODE: RX129412-13				MOTOR FLANGE CODE: RX128581-02																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
For the installation, please refer to User Manual DRP (182/009)								<table><tr><td colspan="2">General tolerance: Js13</td><td>Cmm</td><td colspan="2">Automatic / manual coordinate-measuring machine</td><td>µm</td><td>Micrometer</td><td>Cr</td><td colspan="2">Calliper rule</td><td>Di</td><td>Dial indicator</td><td>Pg</td><td>Plug gauge</td></tr><tr><td colspan="2">HOUSING</td><td colspan="2">requirement</td><td colspan="2">measure</td><td colspan="2">HOUSING</td><td colspan="2">requirement</td><td colspan="2">measure</td><td colspan="2">MOTOR FLANGE</td><td colspan="2">requirement</td><td colspan="2">measure</td></tr><tr><td></td><td>E</td><td>540</td><td>0 -0,1</td><td>Cmm</td><td>539,953</td><td></td><td>O1</td><td>35</td><td>Cr</td><td>35</td><td></td><td>Ø</td><td>B1</td><td>115</td><td>µm</td><td>114,977</td></tr><tr><td></td><td>G</td><td>650</td><td>+0,2 -0,2</td><td>Cmm</td><td>650,012</td><td></td><td>P11</td><td>80</td><td>Cr</td><td>80</td><td></td><td>Ø</td><td>C1</td><td>35</td><td>+0,05 +0,025</td><td>µm</td><td>35,05</td></tr><tr><td>//</td><td>g</td><td>0,045</td><td></td><td>Cmm</td><td>0,02</td><td></td><td>P12</td><td>80</td><td>Cr</td><td>80</td><td></td><td></td><td>D1</td><td>8</td><td>Cr</td><td>8,55</td></tr><tr><td>//</td><td>t</td><td>0,045</td><td></td><td>Cmm</td><td>0,003</td><td></td><td>O2</td><td>35</td><td>Cr</td><td>35</td><td></td><td>Ø</td><td>S1</td><td>200</td><td>Cr</td><td>200</td></tr><tr><td>//</td><td>u</td><td>0,035</td><td></td><td>Cmm</td><td>0,002</td><td></td><td>P21</td><td>80</td><td>Cr</td><td>80</td><td></td><td>Ø</td><td>Y1</td><td>M12</td><td>Pg</td><td>M12</td></tr><tr><td>//</td><td>v</td><td>0,045</td><td></td><td>Cmm</td><td>0,002</td><td></td><td>P22</td><td>80</td><td>Cr</td><td>80</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>W</td><td>135</td><td></td><td>Cmm</td><td>135,001</td><td></td><td>Ø</td><td>T</td><td>M20</td><td>Pg</td><td>M20</td><td></td><td>Ø</td><td>B2</td><td>115</td><td>µm</td><td>114,98</td></tr><tr><td>//</td><td>w</td><td>0,035</td><td></td><td>Cmm</td><td>0,001</td><td colspan="4">OUTPUT PINION</td><td></td><td>Ø</td><td>C2</td><td>35</td><td>+0,05 +0,025</td><td>µm</td><td>35,05</td></tr><tr><td></td><td>X</td><td>135</td><td></td><td>Cmm</td><td>135,01</td><td colspan="4">Pinion 1</td><td colspan="4">O1223</td><td></td><td>D2</td><td>8</td><td>Cr</td><td>8,55</td></tr><tr><td>//</td><td>x</td><td>0,035</td><td></td><td>Cmm</td><td>0,001</td><td colspan="4">Span dimension over 3 teeth</td><td colspan="4"></td><td></td><td>Ø</td><td>S2</td><td>200</td><td>Cr</td><td>200</td></tr><tr><td></td><td>H</td><td>270</td><td>+0,04 -0,04</td><td>Cmm</td><td>270,011</td><td></td><td>G1</td><td>39,25</td><td>0 -0,03</td><td>Cmm</td><td>39,235</td><td></td><td>Ø</td><td>Y2</td><td>M12</td><td>Pg</td><td>M12</td></tr><tr><td>//</td><td>h</td><td>0,02</td><td></td><td>Cmm</td><td>0,008</td><td></td><td>g1</td><td>0,022</td><td></td><td>Di</td><td>0,01</td><td colspan="2"></td><td colspan="2">Line</td><td colspan="2">Stiffness</td></tr><tr><td></td><td>A1</td><td>348,5</td><td></td><td>Cmm</td><td>349,37</td><td></td><td colspan="4">Pinion 2</td><td colspan="4">O1215</td><td colspan="2">Torsional stiffness (Nm/arcmin)</td><td>1</td><td>473,03</td></tr><tr><td></td><td>L1</td><td>101</td><td></td><td>Cmm</td><td>101,022</td><td></td><td colspan="4">Span dimension over 3 teeth</td><td colspan="4"></td><td colspan="2">Radial stiffness (N/µm)</td><td>2</td><td>473,03</td></tr><tr><td></td><td>A2</td><td>348,5</td><td></td><td>Cmm</td><td>349,41</td><td></td><td>G2</td><td>39,25</td><td>0 -0,03</td><td>Cmm</td><td>39,235</td><td colspan="2"></td><td colspan="2">Noise level</td><td>1</td><td>871</td></tr><tr><td></td><td>L2</td><td>101</td><td></td><td>Cmm</td><td>100,999</td><td></td><td>g2</td><td>0,022</td><td></td><td>Di</td><td>0,01</td><td colspan="2"></td><td colspan="2">@1600 rpm input (dB(A))</td><td>2</td><td>1003</td></tr><tr><td colspan="4" rowspan="3">SPECIFIC REMARKS:</td><td colspan="4"></td><td colspan="4">No-load input torque</td><td colspan="4"></td><td colspan="4"></td></tr><tr><td colspan="4"></td><td colspan="4">Line 1</td><td colspan="4">0,8 Nm</td><td colspan="4"></td></tr><tr><td colspan="4"></td><td colspan="4">Line 2</td><td colspan="4">0,8 Nm</td><td colspan="4"></td></tr><tr><td colspan="4" rowspan="3">Product images are for illustrative purposes only.</td><td colspan="4"></td><td colspan="4">Date: 13/02/2017</td><td colspan="4">Visa: J ONGANER</td><td colspan="4"></td></tr><tr><td colspan="4"></td><td colspan="4">Version: A</td><td colspan="4"></td><td colspan="4"></td></tr><tr><td colspan="4"></td><td colspan="4"></td><td colspan="4"></td><td colspan="4"></td></tr><tr><td colspan="4">REDEX</td><td colspan="4">ZI-BP79 F45210 FERRIERES www.redex.fr</td><td colspan="4">Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr</td><td colspan="4">REDEX</td><td colspan="4">ZI-BP79 F45210 FERRIERES www.redex.fr</td><td colspan="4">Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr</td></tr></table>				General tolerance: Js13		Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer	Cr	Calliper rule		Di	Dial indicator	Pg	Plug gauge	HOUSING		requirement		measure		HOUSING		requirement		measure		MOTOR FLANGE		requirement		measure			E	540	0 -0,1	Cmm	539,953		O1	35	Cr	35		Ø	B1	115	µm	114,977		G	650	+0,2 -0,2	Cmm	650,012		P11	80	Cr	80		Ø	C1	35	+0,05 +0,025	µm	35,05	//	g	0,045		Cmm	0,02		P12	80	Cr	80			D1	8	Cr	8,55	//	t	0,045		Cmm	0,003		O2	35	Cr	35		Ø	S1	200	Cr	200	//	u	0,035		Cmm	0,002		P21	80	Cr	80		Ø	Y1	M12	Pg	M12	//	v	0,045		Cmm	0,002		P22	80	Cr	80								W	135		Cmm	135,001		Ø	T	M20	Pg	M20		Ø	B2	115	µm	114,98	//	w	0,035		Cmm	0,001	OUTPUT PINION					Ø	C2	35	+0,05 +0,025	µm	35,05		X	135		Cmm	135,01	Pinion 1				O1223					D2	8	Cr	8,55	//	x	0,035		Cmm	0,001	Span dimension over 3 teeth									Ø	S2	200	Cr	200		H	270	+0,04 -0,04	Cmm	270,011		G1	39,25	0 -0,03	Cmm	39,235		Ø	Y2	M12	Pg	M12	//	h	0,02		Cmm	0,008		g1	0,022		Di	0,01			Line		Stiffness			A1	348,5		Cmm	349,37		Pinion 2				O1215				Torsional stiffness (Nm/arcmin)		1	473,03		L1	101		Cmm	101,022		Span dimension over 3 teeth								Radial stiffness (N/µm)		2	473,03		A2	348,5		Cmm	349,41		G2	39,25	0 -0,03	Cmm	39,235			Noise level		1	871		L2	101		Cmm	100,999		g2	0,022		Di	0,01			@1600 rpm input (dB(A))		2	1003	SPECIFIC REMARKS:								No-load input torque																Line 1				0,8 Nm												Line 2				0,8 Nm								Product images are for illustrative purposes only.								Date: 13/02/2017				Visa: J ONGANER												Version: A																												REDEX				ZI-BP79 F45210 FERRIERES www.redex.fr				Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr				REDEX				ZI-BP79 F45210 FERRIERES www.redex.fr				Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr			
												General tolerance: Js13		Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer	Cr	Calliper rule		Di	Dial indicator	Pg	Plug gauge																																																																																																																																																																																																																																																																																																																																																																																																																																																	
												HOUSING		requirement		measure		HOUSING		requirement		measure		MOTOR FLANGE		requirement		measure																																																																																																																																																																																																																																																																																																																																																																																																																																														
													E	540	0 -0,1	Cmm	539,953		O1	35	Cr	35		Ø	B1	115	µm	114,977																																																																																																																																																																																																																																																																																																																																																																																																																																														
													G	650	+0,2 -0,2	Cmm	650,012		P11	80	Cr	80		Ø	C1	35	+0,05 +0,025	µm	35,05																																																																																																																																																																																																																																																																																																																																																																																																																																													
												//	g	0,045		Cmm	0,02		P12	80	Cr	80			D1	8	Cr	8,55																																																																																																																																																																																																																																																																																																																																																																																																																																														
												//	t	0,045		Cmm	0,003		O2	35	Cr	35		Ø	S1	200	Cr	200																																																																																																																																																																																																																																																																																																																																																																																																																																														
												//	u	0,035		Cmm	0,002		P21	80	Cr	80		Ø	Y1	M12	Pg	M12																																																																																																																																																																																																																																																																																																																																																																																																																																														
												//	v	0,045		Cmm	0,002		P22	80	Cr	80																																																																																																																																																																																																																																																																																																																																																																																																																																																				
													W	135		Cmm	135,001		Ø	T	M20	Pg	M20		Ø	B2	115	µm	114,98																																																																																																																																																																																																																																																																																																																																																																																																																																													
//	w	0,035		Cmm	0,001	OUTPUT PINION					Ø	C2	35	+0,05 +0,025	µm	35,05																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	X	135		Cmm	135,01	Pinion 1				O1223					D2	8	Cr	8,55																																																																																																																																																																																																																																																																																																																																																																																																																																																								
//	x	0,035		Cmm	0,001	Span dimension over 3 teeth									Ø	S2	200	Cr	200																																																																																																																																																																																																																																																																																																																																																																																																																																																							
	H	270	+0,04 -0,04	Cmm	270,011		G1	39,25	0 -0,03	Cmm	39,235		Ø	Y2	M12	Pg	M12																																																																																																																																																																																																																																																																																																																																																																																																																																																									
//	h	0,02		Cmm	0,008		g1	0,022		Di	0,01			Line		Stiffness																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	A1	348,5		Cmm	349,37		Pinion 2				O1215				Torsional stiffness (Nm/arcmin)		1	473,03																																																																																																																																																																																																																																																																																																																																																																																																																																																								
	L1	101		Cmm	101,022		Span dimension over 3 teeth								Radial stiffness (N/µm)		2	473,03																																																																																																																																																																																																																																																																																																																																																																																																																																																								
	A2	348,5		Cmm	349,41		G2	39,25	0 -0,03	Cmm	39,235			Noise level		1	871																																																																																																																																																																																																																																																																																																																																																																																																																																																									
	L2	101		Cmm	100,999		g2	0,022		Di	0,01			@1600 rpm input (dB(A))		2	1003																																																																																																																																																																																																																																																																																																																																																																																																																																																									
SPECIFIC REMARKS:								No-load input torque																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
								Line 1				0,8 Nm																																																																																																																																																																																																																																																																																																																																																																																																																																																														
								Line 2				0,8 Nm																																																																																																																																																																																																																																																																																																																																																																																																																																																														
Product images are for illustrative purposes only.								Date: 13/02/2017				Visa: J ONGANER																																																																																																																																																																																																																																																																																																																																																																																																																																																														
								Version: A																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
REDEX				ZI-BP79 F45210 FERRIERES www.redex.fr				Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr				REDEX				ZI-BP79 F45210 FERRIERES www.redex.fr				Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr																																																																																																																																																																																																																																																																																																																																																																																																																																																						