

KRP		Page
Scheda di prestazione	RX183-006-A	1/2
CLIENTE:	MECOF	RIF. ORDINE CLIENTE: 51 MECOF
DISTRIBUTORE:	ANDANTEX S.r.l	ORDINE INTERNO: 211554
DESIGNAZIONE:	KRP3+M.31.3.H.28/38	NUMERO DI SERIE: 900319
RIFERIMENTO:	RX129016-12	RIFERIMENTO DELLA FLANGIA MOTORE: RX128581-13

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)

OSSERVAZIONE SPECIFICA:

Le immagini dei prodotti sono a carattere puramente illustrativo

KRP

Scheda di prestazione

RX183-006-A

Page

2/2

INTERFACCE E DIMENSIONI ESTERNE:

SN: 900319

Technical drawing of the KRP3+M.31.3.H.28/38 gearbox showing external dimensions and features. The drawing includes a side view with dimensions A, B, C, D, E1, E2, L, and a top view showing the output gear with dimensions G1 and g1. The drawing also shows the input shaft with dimensions 4 x Y on PCD S and n x H on PCD J.

General tolerance: Js13				Cmm		Automatic / manual coordinate-measuring machine				µm		Micrometer		Cr		Calliper rule		Di		Dial indicator		Pg		Plug gauge							
CASSA ESTERNA										PIGNONE IN USCITA										FLANGIA DEL MOTORE											
		richiesta				misurata						richiesta				misurata						richiesta				misurata					
						M6757										O2387															
		E1		255h7 ⁰ _{-0,052}		µm		254.99		Scostamento (su 3 denti)										Ø		B		180G6 ^{+0,039} _{+0,014}		µm		180.02			
		E2		255h7 ⁰ _{-0,052}		µm		254.995				G1		39,25 ⁰ _{-0,03}		Cmm		39.23		Ø		C		38F7 ^{+0,05} _{+0,025}		µm		38.04			
		n x H on PCD J		16 Ø13,5 on PCD 280		Cr		OK				↗		g1		0,022		Di		0,01				D		8		Cr		8.49	
Cr																Ø		S1		215		Cr		215							
		A		328,5		µm		329.53		Coppia in ingresso a vuoto										Ø		Y1		M12		Pg		OK			
		L		121		µm		120.93				linea 1				1 Nm															
																				Livello di rumore											
														Linea		Rigidità						@1600 rpm entrata (dB(A))				62,5					
												Rigidità torsionale (Nm/arcmin)				1		473,03													
												Rigidità radiale (N/µm)				1		1086													

Date: 28/06/2017

Visa: J ONGANER

Version: A