

KRP		Page
PERFORMANCE SHEET	RX183-006-A	1/2
CUSTOMER:	FIVES	CUSTOMER ORDER REF: 27280-00 FIVES
DISTRIBUTOR:	ANDANTEX INCORPORATED	REDEX ORDER REF: 211815
DESIGNATION:	KRP2+R.10.4.H	SERIAL NUMBER: 900363
CODE:	RX128908-03	MOTOR FLANGE CODE: RX129551-05

For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:
* Accepted according the derogation RX 9370

Product images are for illustrative purposes only.

KRP

PERFORMANCE SHEET

RX183-006-A

Page 2/2

EXTERNAL DIMENSIONS & INTERFACES:

SN: 900363

General tolerance: Js13				Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge			
HOUSING								OUTPUT PINION						MOTOR FLANGE						
		requirement			measure				requirement			measure				requirement			measure	
					A1763							O2350							A2873	
			E1	212h7 ⁰ _{-0,046}	µm	211.98	Span dimension over 4 teeth								Ø	B	130 ^{+0,054} _{+0,014}	µm	130.04	
			E2	200h7 ⁰ _{-0,046}	µm	199.985			G1	44,27 ⁰ _{-0,03}	Cmm	44,255			Ø	C	32 ^{+0,05} _{+0,025}	µm	32.03	
		n x H on PCD J		12 Ø9 on PCD 233		Cr	OK		↗	g1	0,022	Di	0,01			D	18	Cr	18	
						Cr										Ø	S1	215	Cr	215
		V	291,5	µm	291.745	No-load input torque								Ø	Y1	M12	Pg	OK		
		L	94	µm	93.94	Line 1			3 Nm											
		Ø	Q1	35 ^{+0,011} _{-0,005}	µm	35.005							Noise level							
		Ø	Q2	35 ^{+0,011} _{-0,005}	µm	35.005				Line	Stiffness		@1100 rpm input (dB(A))			71,5 *				
							Torsional stiffness (Nm/arcmin)		1	243,75										
							Radial stiffness (N/µm)		1	466										