

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 900886



GEHÄUSE					GEHÄUSE					MOTORFLANSCH								
Sollwert					Istwert		Sollwert					Istwert		Sollwert			Istwert	
					A4205													
Y2 M6x12 Pg OK					L1 60 Cr 60					Ø B 181 µm 180.95								
Ø S2 165 +0,1 -0,1 Cr 165					J 130 Cr 130					Ø C 38 +0,05 +0,025 µm 38.05								
A 295 µm 295.81					K 11 Cr 11					D 8 Cr 8.5								
E 240 Cr 240					2 x 4Ø Y4 M6x12 Pg OK					Ø S1 215 Cr 215								
O 15 Cr 15					F1 40 Cr 40					Ø Y1 M12 Pg OK								
P1 30 Cr 30					F2 24 Cr 24					Leerlaufdrehmoment								
P2 30 Cr 30					2 x 1Ø Y7 10 µm 10													
P3 30 Cr 30					2 x 4Ø Y6 15,5 µm 15.5					Linie 1 0,5 Nm								
P4 30 Cr 30					2 x 5Ø Y5 24 µm 24					Verdrehsteifigkeit (Nm/arcmin) 1 243,75								
T 14 Cr 14					M H6 10 +0,009 0 Cmm 10,001													
U 26 Cr 26					⊥ m 0,05 Cmm 0,016					Radiale Steifigkeit (N/µm) 1 410								
2 x 1Ø Y3 M6x12 Pg OK					N 55 +0,1 -0,1 Cmm 55,04													
R 186 +0,2 +0,1 Cmm 186,183 A					W 110 +0,02 -0,02 Cmm 110,005													
⊙ r 0,1 Cmm 0,06					// w 0,03 /A Cmm 0,001													

ABTRIEBSRITZEL						Geräuschpegel	
	N686				@1100 rpm Eintrieb (dB(A))	64,5	
Zahnweite (über 4 Zähne)							
	G1	44,27 ⁰ _{-0,03}	<i>Cmm</i>	44.255			
	g1	0,022	<i>Di</i>	0,005			

Von: C DE MIRANDA

7

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr