

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 900888



GEHÄUSE					GEHÄUSE					MOTORFLANSCH																					
Sollwert					Istwert		Sollwert					Istwert		Sollwert			Istwert														
					A4207																										
Y2					M6x12		Pg		OK							Ø		B		181		µm		180.95							
Ø					S2		165 ^{+0,1} _{-0,1}		Cr		165							Ø		C		38 ^{+0,05} _{+0,025}		µm		38.05					
A					295		µm		295.72							K		11		Cr		11									
E					240		Cr		240		2 x 4Ø		Y4		M6x12		Pg		OK												
O					15		Cr		15							F1		40		Cr		40									
P1					30		Cr		30							F2		24		Cr		24									
P2					30		Cr		30		2 x 1Ø		Y7		10		µm		10												
P3					30		Cr		30		2 x 4Ø		Y6		15,5		µm		15.5												
P4					30		Cr		30		2 x 5Ø		Y5		24		µm		24												
T					14		Cr		14							M H6		10 ^{+0,009} ₀		Cmm		10,004				Linie		Steifigkeit			
U					26		Cr		26							⊥		m		0,05		Cmm		0,015		Verdrehsteifigkeit (Nm/arcmin)		1		243,75	
2 x 1Ø					Y3		M6x12		Pg		OK							N		55 ^{+0,1} _{-0,1}		Cmm		55,025							
R					186 ^{+0,2} _{+0,1}		Cmm		186,184		A							W		110 ^{+0,02} _{-0,02}		Cmm		110,004		Radiale Steifigkeit (N/µm)		1		446	
⊙					r		0,1		Cmm		0,064							//		w		0,03		/A		Cmm		0			

ABTRIEBSRITZEL						Geräuschpegel	
	N683				@1100 rpm Eitrieb (dB(A))	66,0	
Zahnweite (über 4 Zähne)							
	G1	44,27 ⁰ _{-0,03}	Cmm	44.26			
	q1	0,022	Di	0,015			

Von: C DE MIRANDA



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr