

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 900891



GEHÄUSE					GEHÄUSE					MOTORFLANSCH						
Sollwert				Istwert		Sollwert				Istwert		Sollwert			Istwert	
				A4209												
Y2 M6x12				Pg	OK	L1 60 Cr 60				Ø B 181 µm			180.91			
Ø S2 165 +0,1 -0,1				Cr	165	J 130 Cr 130				Ø C 38 +0,05 +0,025 µm			38.05			
A 295				µm	295.83	K 11 Cr 11				D 8 Cr			8.5			
E 240				Cr	240	2 x 4Ø	Y4 M6x12	Pg	OK	Ø S1 215 Cr			215			
O 15				Cr	15	F1 40 Cr 39.78				Ø Y1 M12 Pg			OK			
P1 30				Cr	30	F2 24 Cr 24.14				Leerlaufdrehmoment						
P2 30				Cr	30	2 x 1Ø	Y7 10 µm	10								
P3 30				Cr	30	2 x 4Ø	Y6 15,5 µm	15.5	Linie 1			0,7 Nm				
P4 30				Cr	30	2 x 5Ø	Y5 24 µm	24	Steifigkeit							
T 14				Cr	14	M H6 10 +0,009 0 Cmm	10									
U 26				Cr	26	⊥	m 0,05 Cmm	0,006	Verdrehsteifigkeit (Nm/arcmin)		1	243,75				
2 x 1Ø	Y3	M6x12	Pg	OK	N 55 +0,1 -0,1 Cmm		55,024									
	R	186 +0,2 +0,1	Cmm	186,186	A	W 110 +0,02 -0,02 Cmm	110,004	Radiale Steifigkeit (N/µm)		1	438					
⊙	r	0,1	Cmm	0,075	//	w 0,03 /A Cmm	0,001									

ABTRIEBSRITZEL						Geräuschpegel	
	N697				@1100 rpm Eintrieb (dB(A))	63,0	
Zahnweite (über 4 Zähne)							
	G1	44,27 ⁰ _{-0,03}	Cmm	44.26			
	g1	0,022	Di	0,01			

Von: C DE MIRANDA

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr