

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	900905
--------------------------------------	-----	--------



CARCASA						PINÓN DE SALIDA				BRIDA MOTOR					
requerida			real			requerida			real		requerida			real	
			A5114						N1430					-	
	E1	212h7 ⁰ _{-0,046}	μm	211.98	Medida cordal entre 4 dientes						∅	B		μm	
	E2	200h7 ⁰ _{-0,046}	μm	199.99		G1	44,27 ⁰ _{-0,03}	Cmm	44.255	∅	C		μm		
n x H on PCD J		12 Ø9 on PCD 233	Cr	OK	↗	g1	0,022	Di	0,005		D		Cr		
			Cr								∅	S1		Cr	
	V	289	μm	289.33	Par entrada sin carga						∅	Y1		Pg	
	L	94	μm	94.58	Línea 1			0,7 Nm							
	Ø Q1	25 ^{+0,009} _{-0,004}	μm	25							Nivel sonoro				
	Ø Q2	25 ^{+0,009} _{-0,004}	μm	25				Línea	Rigidez	@1600 rpm entrada (dB(A))			71,5		

	Rigidez torsional (Nm/arcmin)	1	243,75
	Rigidez radial (N/μm)	1	417

Revisado: C DE MIRANDA

