

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	900907
--------------------------------------	-----	--------



CARCASA					PIÑÓN DE SALIDA					BRIDA MOTOR				
requerida					real		requerida					real		
					A5159							-		
	E1	152h7 ⁰ _{-0,04}	µm	151,99	Medida cordal entre 3 dientes					Ø	B		µm	
	E2	140h7 ⁰ _{-0,04}	µm	139,98		G1	23,28 ⁰ _{-0,03}	Cmm	23,27	Ø	C		µm	
n x H		12 Ø6,5 on	Cr	12 Ø6,5 on	↗	g1	0,021	Di	0,01		D		Cr	
on PCD J		PCD 168	Cr	PCD 168						Ø	S1		Cr	
	V	228,5	µm	228,41	Par entrada sin carga					Ø	Y1		Pg	
	L	71	µm	70,74	Línea 1				0,5 Nm					
Ø	Q1	20 ^{+0,009} _{-0,004}	µm	19,996						Nivel sonoro				
Ø	Q2	20 ^{+0,009} _{-0,004}	µm	20,005			Línea	Rigidez		@1600 rpm entrada (dB(A))			71,5	

	Rigidez torsional (Nm/arcmin)	1	81,39
	Rigidez radial (N/μm)	1	326

Revisado: C DE MIRANDA

A handwritten signature in black ink, appearing to be "J. D.", written over a horizontal line. The signature is stylized with a large loop for the first letter.

REDEX

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr