

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 900968



GEHÄUSE					GEHÄUSE					MOTORFLANSCH				
Sollwert				Istwert	Sollwert				Istwert	Sollwert				Istwert
				M5447		L1	81	Cr	81					
	Y2	M8x16	Pg	OK		L2	79	Cr	79	Ø	B	181	µm	181
Ø	S2	234 ^{+0,1} _{-0,1}	Cr	234		J	185	Cr	185	Ø	C	38 ^{+0,05} _{+0,025}	µm	38.04
	A	540,5	µm	541.34		K	15	Cr	15		D	8	Cr	8.5
	E	320	Cr	320	2 x 4Ø	Y4	M10x13	Pg	OK	Ø	S1	215	Cr	215
	O	20	Cr	20		F1	60	Cr	60	Ø	Y1	M12	Pg	OK
	P1	40	Cr	40		F2	30	Cr	30.3	Leerlaufdrehmoment				
	P2	40	Cr	40	2 x 1Ø	Y7	14	µm	14					
	P3	40	Cr	40	2 x 4Ø	Y6	22	µm	22	Linie 1				0,5 Nm
	P4	40	Cr	40	2 x 5Ø	Y5	33	µm	33					
	T	20	Cr	20		M H6	15 ^{+0,011} ₀	Cmm	15,01					
	U	37	Cr	37	⊥	m	0,05	Cmm	0,013	Verdrehsteifigkeit (Nm/arcmin)		1	574,81	
2 x 1Ø	Y3	M10x13	Pg	OK		N	72,5 ^{+0,1} _{-0,1}	Cmm	72,452					
	R	255 ^{+0,2} _{+0,1}	Cmm	255,136	A	W	158 ^{+0,035} _{-0,035}	Cmm	158,003	Radiale Steifigkeit (N/µm)		1	1274	
⊙	r	0,1	Cmm	0,021	//	w	0,03	/A	Cmm					0,006

ABTRIEBSRITZEL					Geräuschpegel	
			N528		@1600 rpm Eintrieb (dB(A))	63,5
Zahnweite (über 3 Zähne)						
		G1	46,9 ⁰ _{-0,03}	<i>Cmm</i>	46,885	
	↗	g1	0,022	<i>Di</i>	0,015	

Von: C DE MIRANDA



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr