

|                                  |     |        |
|----------------------------------|-----|--------|
| INTERFACCE E DIMENSIONI ESTERNE: | SN: | 901105 |
|----------------------------------|-----|--------|



| CASSA ESTERNA                     |    |                              |     |          |       | CASSA ESTERNA |                                  |     |         | FLANGIA DEL MOTORE              |     |                                        |        |        |          |        |
|-----------------------------------|----|------------------------------|-----|----------|-------|---------------|----------------------------------|-----|---------|---------------------------------|-----|----------------------------------------|--------|--------|----------|--------|
| richiesta                         |    |                              |     | misurata |       | richiesta     |                                  |     |         | misurata                        |     | richiesta                              |        |        | misurata |        |
|                                   |    |                              |     | A6547    |       |               |                                  |     |         |                                 |     |                                        |        |        |          |        |
| Y2 M8x15                          |    |                              |     | Pg       | M8x15 | L2 70         |                                  |     |         | Cr                              | 75  | Ø B 180G6 <sup>+0,039<br/>+0,014</sup> |        |        | µm       | 180,02 |
| Ø S2 200 <sup>+0,1<br/>-0,1</sup> |    |                              |     | Cr       | 200   | J 160         |                                  |     |         | Cr                              | 160 | Ø C 38F7 <sup>+0,05<br/>+0,025</sup>   |        |        | µm       | 38,05  |
| A 389,5                           |    |                              |     | µm       | 389,6 | K 13          |                                  |     |         | Cr                              | 13  | D 8                                    |        |        | Cr       | 8,5    |
| E 290                             |    |                              |     | Cr       | 290   | 2 x 4Ø        | Y4 M8x15                         | Pg  | M8x15   | Ø S1 215                        |     |                                        | Cr     | 215    |          |        |
| O 25                              |    |                              |     | Cr       | 25    | F1 50         |                                  |     |         | Cr                              | 50  | Ø Y1 M12                               |        |        | Pg       | M12    |
| P1 35                             |    |                              |     | Cr       | 35    | F2 25         |                                  |     |         | Cr                              | 25  | Coppia in ingresso a vuoto             |        |        |          |        |
| P2 35                             |    |                              |     | Cr       | 35    | 2 x 1Ø        | Y7 12                            | µm  | 12      |                                 |     |                                        |        |        |          |        |
| P3 35                             |    |                              |     | Cr       | 35    | 2 x 4Ø        | Y6 17,5                          | µm  | 17,5    | linea 1                         |     |                                        | 0,8 Nm |        |          |        |
| P4 35                             |    |                              |     | Cr       | 35    | 2 x 5Ø        | Y5 26                            | µm  | 26      | Linea Rigidità                  |     |                                        |        |        |          |        |
| T 17                              |    |                              |     | Cr       | 17    | M H6          | 12 <sup>+0,011<br/>0</sup>       | Cmm | 12      |                                 |     |                                        |        |        |          |        |
| U 32                              |    |                              |     | Cr       | 32    | ⊥             | m 0,05                           | Cmm | 0,014   | Rigidità torsionale (Nm/arcmin) |     |                                        | 1      | 473,03 |          |        |
| 2 x 1Ø                            | Y3 | M8x15                        | Pg  | M8x15    |       | N             | 71,5 <sup>+0,1<br/>-0,1</sup>    | Cmm | 71,518  |                                 |     |                                        |        |        |          |        |
|                                   | R  | 226 <sup>+0,2<br/>+0,1</sup> | Cmm | 226,135  | A     | W             | 135 <sup>+0,035<br/>-0,035</sup> | Cmm | 135,004 | Rigidità radiale (N/µm)         |     |                                        | 1      | 867    |          |        |
| ⊙                                 | r  | 0,1                          | Cmm | 0,05     | //    | w             | 0,03 /A                          | Cmm | 0,007   |                                 |     |                                        |        |        |          |        |

|                          |   |    |                                     |     |       |                           |      |
|--------------------------|---|----|-------------------------------------|-----|-------|---------------------------|------|
| PIGNONE IN USCITA        |   |    |                                     |     |       | Livello di rumore         |      |
|                          |   |    |                                     |     | N1870 | @1600 rpm entrata (dB(A)) | 61,5 |
| Scostamento (su 3 denti) |   |    |                                     |     |       |                           |      |
|                          |   | G1 | 39,25 <sup>0</sup> <sub>-0,03</sub> | Cmm | 39,23 |                           |      |
|                          | ↗ | a1 | 0,022                               | Di  | 0,01  |                           |      |

Visa: C DE MIRANDA

**REDEX** ZI-BP79 Tel: +33 2 38 94 42 00  
F45210 FERRIERES Fax: +33 2 38 94 42 99  
www.redex.fr Email: info@redex.fr