

INTERFACCE E DIMENSIONI ESTERNE:	SN:	901106
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			A6549					L1	75	Cr	75					
	Y2	M8x15	Pg	M8x15		L2	70	Cr	70		Ø	B	180G6 ^{+0,039 +0,014}	µm	180,03	
Ø	S2	200 ^{+0,1 -0,1}	Cr	200		J	160	Cr	160		Ø	C	38F7 ^{+0,05 +0,025}	µm	38,05	
	A	389,5	µm	389,6		K	13	Cr	13			D	8	Cr	8,5	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215	
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12	
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			0,8 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26	Linea					Rigidità	
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12							
	U	32	Cr	32	⊥	m	0,05	Cmm	0,012	Rigidità torsionale (Nm/arcmin)			1		473,03	
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1 -0,1}	Cmm	71,494							
	R	226 ^{+0,2 +0,1}	Cmm	226,135	A	W	135 ^{+0,035 -0,035}	Cmm	135,007	Rigidità radiale (N/µm)			1		871	
⊙	r	0,1	Cmm	0,046	//	w	0,03	/A	Cmm							

PIGNONE IN USCITA					Livello di rumore	
			N1876		@1600 rpm entrata (dB(A))	65,5
Scostamento (su 3 denti)						
		G1	39,25 ⁰ _{-0,03}	Cmm	39,23	
	↗	g1	0,022	Di	0,01	

Visa: C DE MIRANDA

REDEX

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr