

INTERFACCE E DIMENSIONI ESTERNE:	SN:	901139
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			A6716					L1	75	Cr	75				
	Y2	M8x15	Pg	OK		L2	70	Cr	70		Ø	B	180G6 ^{+0,039 +0,014}	µm	180,02
Ø	S2	200 ^{+0,1 -0,1}	Cr	200		J	160	Cr	160		Ø	C	38F7 ^{+0,05 +0,025}	µm	38,04
	A	389,5	µm	389,8		K	13	Cr	13			D	8	Cr	8,48
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	OK		Ø	S1	215	Cr	215
	O	25	Cr	25		F1	50	Cr	50,19		Ø	Y1	M12	Pg	OK
	P1	35	Cr	35		F2	25	Cr	24,4	Coppia in ingresso a vuoto					
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12						
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			0,9 Nm		
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26						
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12						
	U	32	Cr	32	⊥	m	0,05	Cmm	0,018	Rigidità torsionale (Nm/arcmin)	1	473,03			
2 x 1 Ø	Y3	M8x15	Pg	OK		N	71,5 ^{+0,1 -0,1}	Cmm	71,532						
	R	226 ^{+0,2 +0,1}	Cmm	226,136	A	W	135 ^{+0,035 -0,035}	Cmm	135,008	Rigidità radiale (N/µm)	1	902			
⊙	r	0,1	Cmm	0,048	//	w	0,03 /A	Cmm	0,003						

PIGNONE IN USCITA						Livello di rumore	
					N1861	@1600 rpm entrata (dB(A))	62,5
Scostamento (su 3 denti)							
		G1	39,25 ⁰ _{-0,03}	Cmm	39,23		
	↗	g1	0,022	Di	0,01		

Visa: C DE MIRANDA 

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr