

INTERFACCE E DIMENSIONI ESTERNE:		SN:	901140
----------------------------------	--	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			A6715					L1	75	Cr	75					
	Y2	M8x15	Pg	OK		L2	70	Cr	70		Ø	B	180G6 ^{+0,039 +0,014}	µm	180,015	
Ø	S2	200 ^{+0,1 -0,1}	Cr	200		J	160	Cr	160		Ø	C	38F7 ^{+0,05 +0,025}	µm	38,025	
	A	389,5	µm	389,71		K	13	Cr	13			D	8	Cr	8,48	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	OK		Ø	S1	215	Cr	215	
	O	25	Cr	25		F1	50	Cr	50,15		Ø	Y1	M12	Pg	OK	
	P1	35	Cr	35		F2	25	Cr	24,5	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			0,8 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26						Linea	Rigidità
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12							
	U	32	Cr	32	⊥	m	0,05	Cmm	0,012	Rigidità torsionale (Nm/arcmin)		1	473,03			
2 x 1 Ø	Y3	M8x15	Pg	OK		N	71,5 ^{+0,1 -0,1}	Cmm	71,52							
	R	226 ^{+0,2 +0,1}	Cmm	226,136	A		W	135 ^{+0,035 -0,035}	Cmm	135,006	Rigidità radiale (N/µm)		1	854		
⊙	r	0,1	Cmm	0,048		//	w	0,03	/A	Cmm						0,002

PIGNONE IN USCITA						Livello di rumore	
					N1871	@1600 rpm entrata (dB(A))	61,5
Scostamento (su 3 denti)							
		G1	39,25 ⁰ _{-0,03}	Cmm	39,22		
	↗	g1	0,022	Di	0,005		

Visa: C DE MIRANDA 

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr