


INTERFACCE E DIMENSIONI ESTERNE:	SN:	901298
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE							
richiesta				misurata		richiesta				misurata		richiesta			misurata		
				B69			L1	60	Cr	60							
	Y2	M6x12	Pg	OK		L2	60	Cr	60		Ø	B	181	µm	180.97		
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		J	130	Cr	130		Ø	C	38 ^{+0,05 +0,025}	µm	38.04		
	A	332	µm	332.87		K	11	Cr	11			D	8	Cr	8.5		
	E	240	Cr	240	2 x 40	Y4	M6x12	Pg	OK		Ø	S1	215	Cr	215		
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	OK		
	P1	30	Cr	30		F2	24	Cr	24.6	Coppia in ingresso a vuoto							
	P2	30	Cr	30	2 x 10	Y7	10	µm	10								
	P3	30	Cr	30	2 x 40	Y6	15,5	µm	15.5	linea 1				1 Nm			
	P4	30	Cr	30	2 x 50	Y5	24	µm	24	Rigidità torsionale (Nm/arcmin)						1	243,75
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10,001								
	U	26	Cr	26	⊥	m	0,05	Cmm	0,008	Rigidità radiale (N/µm)						1	506
2 x 10	Y3	M6x12	Pg	OK		N	55 ^{+0,1 -0,1}	Cmm	54,933								
	R	186 ^{+0,2 +0,1}	Cmm	186,173	A	W	110 ^{+0,02 -0,02}	Cmm	110,003								
⊙	r	0,1	Cmm	0,074	//	w	0,03	/A	Cmm								

PIGNONE IN USCITA						Livello di rumore	
					N2138	@1600 rpm entrata (dB(A))	67,5
Scostamento (su 4 denti)							
		G1	44,27 ⁰ _{-0,03}	Cmm	44.26		
	↗	g1	0,022	Di	0,01		

Visa: C DE MIRANDA 

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr