

KRP		Page
Scheda di prestazione	RX183-006-A	1/2
CLIENTE:	MECOF	RIF. ORDINE CLIENTE: 761 MECOF
DISTRIBUTORE:	ANDANTEX S.r.l	ORDINE INTERNO: 212534
DESIGNAZIONE:	KRP3+M.31.3.H.28/38	NUMERO DI SERIE: 901327
RIFERIMENTO:	RX129016-12	RIFERIMENTO DELLA FLANGIA MOTORE: RX128581-13

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)

OSSERVAZIONE SPECIFICA:

Le immagini dei prodotti sono a carattere puramente illustrativo.

KRP		Page
Scheda di prestazione	RX183-006-A	2/2
INTERFACCE E DIMENSIONI ESTERNE:		SN: 901327

Technical drawing of a pump assembly showing a cross-section and a top view of the gear.

Dimensions and features labeled:

- $\varnothing B$: Outer diameter of the pump head.
- $\varnothing C$: Diameter of the central shaft.
- $4 \times Y$ on PCD S : Four ports on the pump head.
- D : Thickness of the pump head.
- A : Height of the pump head.
- $\varnothing E1$: Diameter of the upper port.
- $n \times H$ on PCD J : Gear teeth on the lower port.
- $\varnothing E2$: Diameter of the lower port.
- L : Height of the lower port.
- $G1$: Gear teeth on the top view.
- $g1$: Gear teeth on the top view.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge	
CASSA ESTERNA						PIGNONE IN USCITA						FLANGIA DEL MOTORE					
		richiesta		misurata				richiesta		misurata				richiesta		misurata	
				A6723						N2197							
		E1	255h7 ⁰ _{-0,052}	µm	254.97	Scostamento (su 3 denti)						Ø	B	180G6 ^{+0,039} _{+0,014}	µm	180.039	
		E2	255h7 ⁰ _{-0,052}	µm	254.98		G1	39,25 ⁰ _{-0,03}	Cmm	39.245	Ø	C	38F7 ^{+0,05} _{+0,025}	µm	38.025		
n x H on PCD J		16 Ø13,5 on PCD 280	Cr	OK	↗	g1	0,022	Di	0.005		D	8	Cr	8.5			
			Cr							Ø	S1	215	Cr	215			
		A	328.5	µm	329	Coppia in ingresso a vuoto						Ø	Y1	M12	Pg	OK	
		L	121	µm	121	linea 1				1 Nm							
										Livello di rumore							
								Linea	Rigidità		@1600 rpm entrata (dB(A))		66.5				
						Rigidità torsionale (Nm/arcmin)		1	473,03								
						Rigidità radiale (N/µm)		1	1089								