

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 901341



GEHÄUSE					GEHÄUSE					MOTORFLANSCH					
Sollwert			Istwert		Sollwert			Istwert		Sollwert			Istwert		
			A1366					L1 51 Cr 51							
	Y2	M6x12	Pg	M6x12		L2	48	Cr	48		Ø	B	131	µm	131
Ø	S2	120 ^{+0,1 -0,1}	Cr	120		J	105	Cr	105		Ø	C	32 ^{+0,05 +0,025}	µm	32,05
	A	264	µm	264,83		K	11	Cr	11			D	8	Cr	8,5
	E	175	Cr	175	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	165	Cr	165
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M10	Pg	M10
	P1	24	Cr	24		F2	24	Cr	24	Leerlaufdrehmoment					
	P2	24	Cr	24	2 x 1 Ø	Y7	10	µm	10						
	P3	24	Cr	24	2 x 4 Ø	Y6	11	µm	11	Linie 1			0,5 Nm		
	P4	24	Cr	24	2 x 5 Ø	Y5	18	µm	18						
	T	14	Cr	14		M H6	8 ^{+0,009 0}	Cmm	8,002						
	U	26	Cr	26	⊥	m	0,05	Cmm	0,02	Verdrehsteifigkeit (Nm/arcmin)		1	81,39		
2 x 1 Ø	Y3	M6x12	Pg	M6x12		N	47 ^{+0,1 -0,1}	Cmm	47,04						
	R	135 ^{+0,2 +0,1}	Cmm	135,162	A	W	80 ^{+0,02 -0,02}	Cmm	80,009	Radiale Steifigkeit (N/µm)		1	302		
⊙	r	0,1	Cmm	0,017	//	w	0,03 /A	Cmm	0,001						

ABTRIEBSRITZEL						Geräuschpegel	
	P1980				@2600 rpm Eintrieb (dB(A))	61,5	
Zahnweite (über 3 Zähne)							
	G1	23,28 ⁰ _{-0,03}	Cmm	23,26			
	g1	0,021	Di	0,01			

Von: C DE MIRANDA



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr