

|                                                                                                 |  |                                       |  |                                                                                                                                            |  |
|-------------------------------------------------------------------------------------------------|--|---------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------|--|
| KRP                                                                                             |  |                                       |  | Page                                                                                                                                       |  |
| PERFORMANCE SHEET                                                                               |  | RX183-006-A                           |  | 1/2                                                                                                                                        |  |
| CUSTOMER: YONG JU PRECISION                                                                     |  | CUSTOMER ORDER REF: RX106325T YONG JU |  | EXTERNAL DIMENSIONS & INTERFACES: SN: 901369                                                                                               |  |
| DISTRIBUTOR:                                                                                    |  | REDEX ORDER REF: 212408               |  |                                                                                                                                            |  |
| DESIGNATION: KRP2+R.31.4.H                                                                      |  | SERIAL NUMBER: 901369                 |  |                                                                                                                                            |  |
| CODE: RX128908-12                                                                               |  | MOTOR FLANGE CODE:                    |  |                                                                                                                                            |  |
| <p>For the installation, please refer to User Manual KRP (182/008)</p> <p>SPECIFIC REMARKS:</p> |  |                                       |  |                                                                                                                                            |  |
|                                                                                                 |  |                                       |  | General tolerance: Js13 Cmm Automatic / manual coordinate-measuring machine μm Micrometer Cr Calliper rule Di Dial indicator Pg Plug gauge |  |
|                                                                                                 |  |                                       |  | HOUSING OUTPUT PINION MOTOR FLANGE                                                                                                         |  |
|                                                                                                 |  |                                       |  | requirement measure requirement measure requirement measure                                                                                |  |
|                                                                                                 |  |                                       |  | A7014 N2148                                                                                                                                |  |
|                                                                                                 |  |                                       |  | Span dimension over 4 teeth                                                                                                                |  |
|                                                                                                 |  |                                       |  | G1 44,27 ±0,03 Cmm 44.25 g1 0,022 Di 0,01                                                                                                  |  |
|                                                                                                 |  |                                       |  | No-load input torque                                                                                                                       |  |
|                                                                                                 |  |                                       |  | Line 1 1 Nm                                                                                                                                |  |
|                                                                                                 |  |                                       |  | Noise level                                                                                                                                |  |
| @1600 rpm input (dB(A)) 70,5                                                                    |  |                                       |  |                                                                                                                                            |  |
| Torsional stiffness (Nm/arcmin) 1 243,75                                                        |  |                                       |  |                                                                                                                                            |  |
| Radial stiffness (N/μm) 1 390                                                                   |  |                                       |  |                                                                                                                                            |  |
| Date: 06/02/2018 Visa: C DE MIRANDA                                                             |  |                                       |  |                                                                                                                                            |  |
| Version: A                                                                                      |  |                                       |  |                                                                                                                                            |  |
| Product images are for illustrative purposes only.                                              |  |                                       |  |                                                                                                                                            |  |

REDEX

ZI-BP79  
F45210 FERRIERES  
www.redex.fr

Tel: +33 2 38 94 42 00  
Fax: +33 2 38 94 42 99  
Email: info@redex.fr

REDEX

ZI-BP79  
F45210 FERRIERES  
www.redex.fr

Tel: +33 2 38 94 42 00  
Fax: +33 2 38 94 42 99  
Email: info@redex.fr