

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 901492



GEHÄUSE					GEHÄUSE					MOTORFLANSCH					
Sollwert			Istwert		Sollwert			Istwert		Sollwert			Istwert		
			A9543					L1	60	Cr	60				
	Y2	M6x12	Pg	OK		L2	60	Cr	60		Ø	B	181	µm	181
Ø	S2	165 ^{+0,1} _{-0,1}	Cr	165		J	130	Cr	130		Ø	C	38 ^{+0,05} _{+0,025}	µm	38.05
	A	295	µm	295		K	11	Cr	11			D	8	Cr	8.5
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	OK		Ø	S1	215	Cr	215
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	OK
	P1	30	Cr	30		F2	24	Cr	24	Leerlaufdrehmoment					
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10						
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15.5	Linie 1			1 Nm		
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24						
	T	14	Cr	14		M H6	10 ^{+0,009} ₀	Cmm	10.004						
	U	26	Cr	26	⊥	m	0,05	Cmm	0.012	Verdrehsteifigkeit (Nm/arcmin)	1	243,75			
2 x 1 Ø	Y3	M6x12	Pg	OK		N	55 ^{+0,1} _{-0,1}	Cmm	54.99						
	R	186 ^{+0,2} _{+0,1}	Cmm	186.173	A	W	110 ^{+0,02} _{-0,02}	Cmm	110.01	Radiale Steifigkeit (N/µm)	1	507			
⊙	r	0,1	Cmm	0.068	//	w	0,03 /A	Cmm	0.004						

ABTRIEBSRITZEL					Geräuschpegel	
			N2443		@1100 rpm Eintrieb (dB(A))	64.5
Zahnweite (über 4 Zähne)						
		G1	44,27 ⁰ _{-0,03}	<i>Cmm</i>	44.25	
	↗	g1	0,022	<i>Di</i>	0.015	

Von: C DE MIRANDA



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr