

INTERFACCE E DIMENSIONI ESTERNE:	SN:	901523
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta				misurata		richiesta				misurata		richiesta			misurata	
				A8826												
Y2 M8x15 Pg OK						L1 75 Cr 75										
Ø S2 200 ^{+0,1} _{-0,1} Cr 200						L2 70 Cr 70				Ø B 180G6 ^{+0,039} _{+0,014} µm 180.035						
Ø S2 200 ^{+0,1} _{-0,1} Cr 200						J 160 Cr 160				Ø C 38F7 ^{+0,05} _{+0,025} µm 38.04						
A 389.5 µm 389.68						K 13 Cr 13				D 8 Cr 8.48						
E 290 Cr 290				2 x 4 Ø		Y4 M8x15 Pg OK				Ø S1 215 Cr 215						
O 25 Cr 25						F1 50 Cr 50				Ø Y1 M12 Pg OK						
P1 35 Cr 35						F2 25 Cr 25				Coppia in ingresso a vuoto						
P2 35 Cr 35				2 x 1 Ø		Y7 12 µm 12										
P3 35 Cr 35				2 x 4 Ø		Y6 17,5 µm 17.5				linea 1			0,8 Nm			
P4 35 Cr 35				2 x 5 Ø		Y5 26 µm 26										
T 17 Cr 17						M H6 12 ^{+0,011} ₀ Cmm 12							Linea	Rigidità		
U 32 Cr 32				⊥		m 0,05 Cmm 0.012				Rigidità torsionale (Nm/arcmin)			1	473,03		
2 x 1 Ø	Y3 M8x15 Pg OK					N 71,5 ^{+0,1} _{-0,1} Cmm 71.496										
R 226 ^{+0,2} _{+0,1} Cmm 226.135				A		W 135 ^{+0,035} _{-0,035} Cmm 135.009				Rigidità radiale (N/µm)			1	923		
⊙	r 0,1 Cmm 0.065			//		w 0,03 /A Cmm 0.004										

PIGNONE IN USCITA						Livello di rumore	
					N2455	@1600 rpm entrata (dB(A))	64.5
Scostamento (su 3 denti)							
		G1	39,25 ⁰ _{-0,03}	Cmm	39.23		
	↗	g1	0,022	Di	0.01		

Visa: C DE MIRANDA 

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr