

KRP		Page
PERFORMANCE SHEET		1/2
CUSTOMER:	KAO MING MACHINERY INDUST	CUSTOMER ORDER REF: RX106331T KAO MING
DISTRIBUTOR:		REDEX ORDER REF: 212480
DESIGNATION:	KRP3+R.31.4.H	SERIAL NUMBER: 901701
CODE:	RX128565-12	MOTOR FLANGE CODE:

For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:

Product images are for illustrative purposes only.

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

KRP		Page
PERFORMANCE SHEET		2/2
EXTERNAL DIMENSIONS & INTERFACES:		SN: 901701

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine			µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge		
HOUSING					OUTPUT PINION							MOTOR FLANGE							
requirement					measure		requirement					measure		requirement				measure	
					A8549							N2602						-	
	E1	255h7 ⁰ _{-0,052}	µm	254,97	Span dimension over 3 teeth							Ø	B			µm			
	E2	255h7 ⁰ _{-0,052}	µm	254,98		G1	39,25 ⁰ _{-0,03}	Cmm	39,24		Ø	C			µm				
n x H on PCD J		16 Ø13,5 on PCD 280		Cr	ok	↗	g1	0,022	Di	0,005			D			Cr			
				Cr								S1			Cr				
	V	337	µm	337,205	No-load input torque							Ø	Y1			Pg			
	L	121	µm	121,142	Line 1					0,8 Nm									
Ø	Q1	30 ^{+0,009} _{-0,004}	µm	30,009								Noise level							
Ø	Q2	30 ^{+0,009} _{-0,004}	µm	30,009					Line	Stiffness		@1600 rpm input (dB(A))				70,0			
					Torsional stiffness (Nm/arcmin)			1	473,03										
					Radial stiffness (N/µm)			1	898										