

KRP

Ficha de resultado

RX183-006-A

1/2

CLIENTE:

AUTOPULIT

REF. PEDIDO:

74212 AUTOPULIT

DISTRIBUIDOR:

PEDIDO INTERNO:

212878

DESIGNACIÓN:

KRP1+R.31.4.H

NÚMERO DE SERIE:

901829

REFERENCIA :

RX129591-12

REFERENCIA DE LA BRIDA MOTOR:

Page

2/2

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

901829

Technical drawing of the KRP1+R.31.4.H pump assembly. The drawing includes a front view, a side view, and a detail of the output gear. Dimensions are indicated as follows: ØQ1 and ØQ2 for the input ports, ØE1 and ØE2 for the mounting flange, V and L for the overall dimensions, G1 for the gear module, and PCD J for the mounting holes. The side view shows the output shaft with dimensions ØC, ØB, and 4 x Y on PCD S.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

µm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

PARA LA INSTALACIÓN, POR FAVOR CONSULTE EL MANUAL DE USUARIO KRP (182/008)

OBSERVACIONES:

CARCASA						PINÓN DE SALIDA				BRIDA MOTOR					
requerida			real			requerida		real		requerida		real			
			B2546					M738				-			
	E1	152h7 ⁰ _{-0,04}	µm	151.98	Medida cordal entre 3 dientes				Ø	B		µm			
	E2	140h7 ⁰ _{-0,04}	µm	139.99		G1	23,28 ⁰ _{-0,03}	Cmm	23.27	Ø	C		µm		
n x H on PCD J		12 Ø6,5 on PCD 168	Cr	12 Ø6,5 on PCD 168		g1	0,021	Di	0.01		D		Cr		
	V	228.5	µm	228.4	Par entrada sin carga				Ø	S1		Cr			
	L	71	µm	70.67	Línea 1				0,2 Nm		Ø	Y1		Pg	
Ø	Q1	20 ^{+0,009} _{-0,004}	µm	20					Nivel sonoro						
Ø	Q2	20 ^{+0,009} _{-0,004}	µm	20.005					@1600 rpm entrada (dB(A))				67.5		
					Rigidez torsional (Nm/arcmin)		1	81,39							
					Rigidez radial (N/µm)		1	325							

Fecha:

13/06/2018

Revisado:

C DE MIRANDA

Versión:

A

Las imágenes del producto son meramente ilustrativas.

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr