

INTERFACCE E DIMENSIONI ESTERNE:	SN:	902265
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			B3407												
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75						
Ø	S2	200 ^{+0,1} _{-0,1}	Cr	200		L2	70	Cr	70		Ø	B	181	µm	181
						J	160	Cr	160		Ø	C	38 ^{+0,05} _{+0,025}	µm	38,05
	A	389,5	µm	389,66		K	13	Cr	13			D	8	Cr	8,5
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12
	P1	35	Cr	35		F2	25	Cr	25						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12	Coppia in ingresso a vuoto					
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1 Nm		
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26						
	T	17	Cr	17		M H6	12 ^{+0,011} ₀	Cmm	12,002			Linea	Rigidità		
2 x 1 Ø	U	32	Cr	32	⊥	m	0,05	Cmm	0,007	Rigidità torsionale (Nm/arcmin)		1	473,03		
	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1} _{-0,1}	Cmm	71,465	Rigidità radiale (N/µm)		1	875		
	R	226 ^{+0,2} _{+0,1}	Cmm	226,129	A	W	135 ^{+0,035} _{-0,035}	Cmm	135,014						
⊙	r	0,1	Cmm	0,037	//	w	0,03	/A Cmm	0,01						

PIGNONE IN USCITA						Livello di rumore	
	M757				@1600 rpm entrata (dB(A))	67,5	
Scostamento (su 3 denti)							
	G1	39,25 ⁰ _{-0,03}	Cmm	39,24			
	g1	0,022	Di	0,01			

Visa: C DE MIRANDA 

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr