

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	902341
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR																
requerida					real		requerida					real		requerida					real							
					B2592																					
Y2					M6x12	Pg	M6x12	L1					60	Cr	60											
Ø					S2	165 ^{+0,1 -0,1}	Cr	165	L2					60	Cr	60	Ø					B	181	µm	180,98	
					A	332	µm	332,87	J					130	Cr	130	Ø					C	38 ^{+0,05 +0,025}	µm	38,05	
					E	240	Cr	240	K					11	Cr	11						D	8	Cr	8,52	
					O	15	Cr	15	2 x 4 Ø					Y4	M6x12	Pg	M6x12	Ø					S1	215	Cr	215
					P1	30	Cr	30	F1					40	Cr	40	Ø					Y1	M12	Pg	M12	
					P2	30	Cr	30	F2					24	Cr	24	Par entrada sin carga									
					P3	30	Cr	30	2 x 1 Ø					Y7	10	µm										10
					P4	30	Cr	30	2 x 4 Ø					Y6	15,5	µm	15,6	Línea 1					0,6 Nm			
					P5	30	Cr	30	2 x 5 Ø					Y5	24	µm	24	Línea					Rígeidez			
					T	14	Cr	14	M H6					10 ^{+0,009 0}	Cmm	10,005										
					U	26	Cr	26	⊥					m	0,05	Cmm	0,004	Rígeidez torsional (Nm/arcmin)					1		243,75	
2 x 1 Ø					Y3	M6x12	Pg	M6x12						N	55 ^{+0,1 -0,1}	Cmm	55,013									
					R	186 ^{+0,2 +0,1}	Cmm	186,172	A					W	110 ^{+0,02 -0,02}	Cmm	110,016	Rígeidez radial (N/µm)					1		440	
⊙					r	0,1	Cmm	0,07	//					w	0,03	/A	Cmm						0,001			

PIÑÓN DE SALIDA					Nivel sonoro	
			M1016		@1600 rpm entrada (dB(A))	66,5
Medida cordal entre 4 dientes						
		G1	44,27 ⁰ _{-0,03}	Cmm	44,255	
	↗	g1	0,022	Di	0,01	



	ZI-BP79 F45210 FERRIERES www.redex.fr	Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr		ZI-BP79 F45210 FERRIERES www.redex.fr	Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr
---	---	---	---	---	---