

INTERFACCE E DIMENSIONI ESTERNE:	SN:	902597
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE							
richiesta			misurata		richiesta			misurata		richiesta			misurata				
			B5982														
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75								
	Ø	S2	200 ^{+0,1 -0,1}	Cr	200		L2	70	Cr	70		Ø	B	180G6 ^{+0,039 +0,014}	µm	180,035	
						J	160	Cr	160		Ø	C	38F7 ^{+0,05 +0,025}	µm	38,05		
	A	389,5	µm	389,5		K	13	Cr	13			D	8	Cr	8,48		
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215		
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12		
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto							
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12								
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1 Nm				
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26	Rigidità torsionale (Nm/arcmin)						1	473,03
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12,005								
	U	32	Cr	32	⊥	m	0,05	Cmm	0,017	Rigidità radiale (N/µm)						1	921
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1 -0,1}	Cmm	71,473								
	R	226 ^{+0,2 +0,1}	Cmm	226,129	A	W	135 ^{+0,035 -0,035}	Cmm	135,007								
⊙	r	0,1	Cmm	0,025	//	w	0,03	/A	Cmm								

PIGNONE IN USCITA						Livello di rumore	
	M2551				@1600 rpm entrata (dB(A))	64,5	
Scostamento (su 3 denti)							
	G1	39,25 ⁰ _{-0,03}	Cmm	39,235			
	g1	0,022	Di	0,015			

Visa: C DE MIRANDA

REDEX

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr