

KRP		Page
Scheda di prestazione	RX183-006-A	1/2
CLIENTE:	TENOVA	RIF. ORDINE CLIENTE: 834 TENOVA
DISTRIBUTORE:	ANDANTEX S.r.l	ORDINE INTERNO: 213798
DESIGNAZIONE:	KRP2+M.31.3.H.28/38	NUMERO DI SERIE: 903131
RIFERIMENTO:	RX128907-12	RIFERIMENTO DELLA FLANGIA MOTORE: RX129461-01

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)

OSSERVAZIONE SPECIFICA:

Le immagini dei prodotti sono a carattere puramente illustrativo.

KRP		Page
Scheda di prestazione	RX183-006-A	2/2
INTERFACCE E DIMENSIONI ESTERNE:		SN: 903131

Technical drawing of the KRP pump assembly, showing a cross-section and a detail view of the gear.

Dimensions and Features:

- ϕB : Outer diameter of the top flange.
- ϕC : Inner diameter of the top flange.
- $4 \times Y$ on PCD S : Four mounting holes on the top flange.
- D : Thickness of the top flange.
- A : Total height of the pump assembly.
- $\phi E1$: Diameter of the main body.
- $n \times H$ on PCD J : n mounting holes on the main body.
- $\phi E2$: Diameter of the lower section.
- L : Height of the lower section.
- $G1$: Gear module.
- $g1$: Gear detail view.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine			µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge												
CASSA ESTERNA							PIGNONE IN USCITA							FLANGIA DEL MOTORE															
		richiesta				misurata				richiesta				misurata				richiesta				misurata							
						B7634								M2396															
		E1		212h7 ⁰ _{-0,046}		µm		211,965		Scostamento (su 4 denti)							Ø		B		131		µm		131				
		E2		200h7 ⁰ _{-0,046}		µm		199,985				G1		44,27 ⁰ _{-0,03}		Cmm		44,25		Ø		C		32 ^{+0,05} _{+0,025}		µm		32,05	
n x H on PCD J		12 Ø9 on PCD 233		Cr		12 Ø9 on		↗		g1		0,022		Di		0,01				D		5		Cr		5,5			
				Cr		PCD 233												Ø		S1		165		Cr		165			
		A		273		µm		274		Coppia in ingresso a vuoto							Ø		Y1		M10		Pg		M10				
		L		94		µm		93,82				linea 1				0,3 Nm													
																	Livello di rumore												
																	@1600 rpm entrata (dB(A))		63,0										