

DRP		Page
Performance sheet	RX183/005-B	1/2
CUSTOMER:	SNK	CUSTOMER ORDER REF: 190220IB-2 SNK
DISTRIBUTOR:	S & F INC	REDEX ORDER REF: 214035
DESIGNATION:	DRP5+R.91.4.H	SERIAL NUMBER: 903145
CODE:	RX129232-33	MOTOR FLANGE CODE:

Mechanical preload data

The preload torque of the gearbox in DUALDRIVE configuration depends on the application data and features of the gearbox.

The preload torque can be increased but must never exceed the maximum value indicated below.

A too important preload torque reduces the efficiency and the life expectancy of the gearbox and the rack.

Optimal preload torque Tp:	Following application
Maximum preload torque:	34,2 Nm

For the installation, please refer to User Manual DRP (182/009)

SPECIFIC REMARKS:

Product images are for illustrative purposes only.

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

DRP		Page
Performance sheet	RX183/005-B	2/2
EXTERNAL DIMENSIONS & INTERFACES:		SN: 903145
The technical drawing illustrates the external dimensions and interfaces of the RX183/005-B motor assembly. It includes a top view, a front view, and a side view. The top view shows the motor housing with dimensions J1, J2, J3, and J4. The front view shows the motor housing with dimensions V1, V2, L1, L2, E, G, G1, G2, and various mounting points (P11, P12, P21, P22). The side view shows the motor housing with dimensions W, X, H, h, and various mounting points (P11, P12, P21, P22). The drawing also includes a detail of the motor housing with dimensions B, C, and D, and a note '4 x Y on PCD S'.		