

|                                                                                                 |  |                                            |  |                                                                                                                                            |  |
|-------------------------------------------------------------------------------------------------|--|--------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------|--|
| KRP                                                                                             |  |                                            |  | Page                                                                                                                                       |  |
| PERFORMANCE SHEET                                                                               |  | RX183-006-A                                |  | 1/2                                                                                                                                        |  |
| CUSTOMER: ELECTROIMPACT                                                                         |  | CUSTOMER ORDER REF: 29112-00 ELECTROIMPACT |  | EXTERNAL DIMENSIONS & INTERFACES: SN: 903163                                                                                               |  |
| DISTRIBUTOR: ANDANTEX INCORPORATED                                                              |  | REDEX ORDER REF: 213886                    |  |                                                                                                                                            |  |
| DESIGNATION: KRP4+M.7.3.H.60/75                                                                 |  | SERIAL NUMBER: 903163                      |  |                                                                                                                                            |  |
| CODE: RX128414-02                                                                               |  | MOTOR FLANGE CODE: RX129604-05             |  |                                                                                                                                            |  |
| <p>For the installation, please refer to User Manual KRP (182/008)</p> <p>SPECIFIC REMARKS:</p> |  |                                            |  |                                                                                                                                            |  |
|                                                                                                 |  |                                            |  | General tolerance: Js13 Cmm Automatic / manual coordinate-measuring machine µm Micrometer Cr Calliper rule Di Dial indicator Pg Plug gauge |  |
|                                                                                                 |  |                                            |  | HOUSING OUTPUT PINION MOTOR FLANGE                                                                                                         |  |
|                                                                                                 |  |                                            |  | requirement measure requirement measure requirement measure                                                                                |  |
|                                                                                                 |  |                                            |  | B10403 M2834                                                                                                                               |  |
|                                                                                                 |  |                                            |  | E1 285h7 <sup>0</sup> <sub>-0,052</sub> µm 284,97 Span dimension over 3 teeth Ø B 251 µm 251,01                                            |  |
|                                                                                                 |  |                                            |  | E2 285h7 <sup>0</sup> <sub>-0,052</sub> µm 284,98 G1 46,9 <sup>0</sup> <sub>-0,03</sub> Cmm 46,89 Ø C T65 µm T65                           |  |
|                                                                                                 |  |                                            |  | n x H on PCD J 16 Ø14 on PCD 310 Cr 16 Ø14 on PCD 310 ↗ g1 0,022 Di 0,01 Ø D 8 Cr 8,52                                                     |  |
|                                                                                                 |  |                                            |  | A 383 µm 383,94 No-load input torque Ø S1 300 Cr 300                                                                                       |  |
|                                                                                                 |  |                                            |  | L 141 µm 141,2 Line 1 8 Nm Ø Y1 M16 Pg M16                                                                                                 |  |
|                                                                                                 |  | Noise level                                |  |                                                                                                                                            |  |
|                                                                                                 |  | @800 rpm input (dB(A)) 60,5                |  |                                                                                                                                            |  |
|                                                                                                 |  | Line Stiffness                             |  |                                                                                                                                            |  |
|                                                                                                 |  | Torsional stiffness (Nm/arcmin) 1 574,81   |  |                                                                                                                                            |  |
|                                                                                                 |  | Radial stiffness (N/µm) 1 1231             |  |                                                                                                                                            |  |
|                                                                                                 |  | Date: 07/05/2019 Visa: C DE MIRANDA        |  |                                                                                                                                            |  |
|                                                                                                 |  | Version: A                                 |  |                                                                                                                                            |  |
| Product images are for illustrative purposes only.                                              |  |                                            |  |                                                                                                                                            |  |
| REDEX                                                                                           |  | ZI-BP79 F45210 FERRIERES www.redex.fr      |  | Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr                                                                         |  |
| REDEX                                                                                           |  | ZI-BP79 F45210 FERRIERES www.redex.fr      |  | Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr                                                                         |  |