

KRP		Page	
Scheda di prestazione		RX183-006-A	
CLIENTE:		47 PIETRO CARNAGHI	
DISTRIBUTORE:		213977	
DESIGNAZIONE:		903430	
RIFERIMENTO:		RX129551-01	

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)	
OSSERVAZIONE SPECIFICA:	
Le immagini dei prodotti sono a carattere puramente illustrativo.	

KRP		Page
Scheda di prestazione		RX183-006-A
INTERFACCE E DIMENSIONI ESTERNE:		SN: 903430

Technical drawing of the KRP RX183-006-A unit, showing front, side, and detail views with dimensions.

Front View Dimensions:

- $\phi Q1$: Diameter of the top left mounting flange.
- $\phi Q2$: Diameter of the top right mounting flange.
- V : Total height of the unit.
- L : Height of the main body section.
- $\phi E1$: Diameter of the upper main body section.
- $\phi E2$: Diameter of the lower main body section.
- $n \times H$ on PCD J: Dimension for the lower main body section.
- $G1$: Diameter of the bottom gear.
- $g1$: Gear module.

Side View Dimensions:

- D : Diameter of the top flange.
- ϕC : Diameter of the central shaft.
- ϕB : Diameter of the main body section.
- $4 \times Y$ on PCD S: Dimension for the four mounting holes on the side flange.

Detail View:

- $4 \times Y$ on PCD S: Dimension for the four mounting holes on the side flange.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge		
CASSA ESTERNA						PIGNONE IN USCITA						FLANGIA DEL MOTORE						
richiesta			misurata			richiesta			misurata			richiesta			misurata			
			B12136						L1125						c315			
	E1	285h7 ⁰ _{-0,052}	µm	284,995		Scostamento (su 3 denti)						Ø	B	180 ^{+0,054} _{+0,014}	µm	180,035		
	E2	285h7 ⁰ _{-0,052}	µm	285			G1	46,9 ⁰ _{-0,03}	Cmm	46,88		Ø	C	38 ^{+0,05} _{+0,025}	µm	38,05		
n x H on PCD J		16 Ø14 on PCD 310	Cr	16 Ø14 on PCD 310		↗	g1	0,022	Di	0,01			D	8	Cr	8,12		
			Cr	PCD 310								Ø	S1	215	Cr	215,09		
			V	414,3	µm	414,23		Coppia in ingresso a vuoto						Ø	Y1	M12	Pg	M12
			L	141	µm	141,22		linea 1			2,5 Nm							
Ø	Q1	35 ^{+0,011} _{-0,005}	µm	34,995								Livello di rumore						
Ø	Q2	35 ^{+0,011} _{-0,005}	µm	35,005					Linea	Rigidità		@1300 rpm entrata (dB(A))			68,5			
						Rigidità torsionale (Nm/arcmin)		1	574,81									
						Rigidità radiale (N/µm)		1	1336									

Date: 22/07/2019

Version: A

Visa: C DE MIRANDA