

[illegible]

General tolerance: Js13	<i>Cmm</i>	Automatic / manual coordinate-measuring machine	μm	Micrometer	<i>Cr</i>	Calliper rule	<i>Di</i>	Dial indicator	<i>Pg</i>	Plug gauge
-------------------------	------------	--	---------------	------------	-----------	---------------	-----------	----------------	-----------	------------

CARCASA		CARCASA		BRIDA MOTOR	
requerido	real	requerido	real	requerido	real

	requerida	real		requerida	real		requerida	real
1			2			3		
4			5			6		
7			8			9		
10			11			12		
13			14			15		
16			17			18		
19			20			21		
22			23			24		
25			26			27		
28			29			30		
31			32			33		
34			35			36		
37			38			39		
40			41			42		
43			44			45		
46			47			48		
49			50			51		
52			53			54		
55			56			57		
58			59			60		
61			62			63		
64			65			66		
67			68			69		
70			71			72		
73			74			75		
76			77			78		
79			80			81		
82			83			84		
85			86			87		
88			89			90		
91			92			93		
94			95			96		
97			98			99		
100			101			102		
103			104			105		
106			107			108		
109			110			111		
112			113			114		
115			116			117		
118			119			120		
121			122			123		
124			125			126		
127			128			129		
130			131			132		
133			134			135		
136			137			138		
139			140			141		
142			143			144		
145			146			147		
148			149			150		
151			152			153		
154			155			156		
157			158			159		
160			161			162		
163			164			165		
166			167			168		
169			170			171		
172			173			174		
175			176			177		
178			179			180		
181			182			183		
184			185			186		
187			188			189		
190			191			192		
193								

				B9246		L1	81	Cr	81					B1631	
	Y2	M8x16	Pg	OK		L2	79	Cr	79		Ø	B	250 ^{+0,061} _{+0,015}	µm	250,043
Ø	S2	234 ^{+0,1} _{-0,1}	Cr	234		J	185	Cr	185		Ø	C	48 ^{+0,05} _{+0,025}	µm	48,04
	V	477	µm	477,22		K	15	Cr	15			D	8	Cr	8,048
	E	320	Cr	320	2 x 4Ø	Y4	M10x13	Pg	OK		Ø	S1	300	Cr	299,97
	O	20	Cr	20		F1	60	Cr	60,5		Ø	Y1	M16	Pg	OK
	P1	40	Cr	40		F2	30	Cr	30						
	P2	40	Cr	40	2 x 1Ø	Y7	14	µm	14	Par entrada sin carga					
	P3	40	Cr	40	2 x 4Ø	Y6	22	µm	22		Línea 1				3 Nm
	P4	40	Cr	40	2 x 5Ø	Y5	22	µm	22						

	F4	40	Cr	40	Z X 50	15	35	μm	35			
	T	20	Cr	20		M H 6	15	$\begin{matrix} +0,011 \\ 0 \end{matrix}$	Cmm	15.003		Línea Rigidez

	U	37	Cr	37			m	0,05	Cmm	0,01	Rigidez torsional (Nm/arcmin)	1	574,81
2 x 10	Y3	M10x13	Pg	OK			N	72,5 ^{+0,1 -0,1}	Cmm	72,513			
	R	255 ^{+0,2 +0,1}	Cmm	255,197	A		W	158 ^{+0,035 -0,035}	Cmm	158,006	Rigidez radial (N/μm)	1	1296
	r	0,1	Cmm	0,024		//	w	0,03 /A	Cmm	0,004			
Ø	Q1	35 ^{+0,011 -0,005}	μm	35,005									
Ø	Q2	35 ^{+0,011 -0,005}	μm	35,005	PIÑÓN DE SALIDA						Nivel sonoro		
	J1	/0	μm	0,01						M2835	@1300 rpm entrada (dB(A))	66,5	

Medida cordal entre 3 dientes					
		G1	46,9 ⁰ _{-0,03}	Cmm	46,89
	↗	g1	0,022	Di	0,01

Fecha: 26/08/2019 Revisado: C DE MIRANDA

Versión: A

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr