

INTERFACCE E DIMENSIONI ESTERNE:	SN:	903990
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			C589					L1	75	Cr	75				C1663	
	Y2	M8x15	Pg	M8x15		L2	70	Cr	70		Ø	B	180H6 ^{+0,025 0}	µm	180,005	
Ø	S2	200 ^{+0,1 -0,1}	Cr	200		J	160	Cr	160		Ø	C	38F7 ^{+0,050 +0,025}	µm	38,04	
	A	389,5	µm	389,95		K	13	Cr	13			D	8	Cr	8,04	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215	
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12	
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26						Linea	Rigidità
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12,011							
	U	32	Cr	32	⊥	m	0,05	Cmm	0,016	Rigidità torsionale (Nm/arcmin)		1	473,03			
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1 -0,1}	Cmm	71,482							
	R	226 ^{+0,2 +0,1}	Cmm	226,145	A	W	135 ^{+0,035 -0,035}	Cmm	135,016	Rigidità radiale (N/µm)		1	978			
⊙	r	0,1	Cmm	0,052	//	w	0,03 /A	Cmm	0,001							

PIGNONE IN USCITA						Livello di rumore	
					L2692	@1600 rpm entrata (dB(A))	62,0
Scostamento (su 3 denti)							
		G1	39,25 ⁰ _{-0,03}	Cmm	39,235		
	↗	g1	0,022	Di	0,015		

Visa: C DE MIRANDA

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr