

DRP		Page
Performance sheet	RX183/005-B	1/2
CUSTOMER:	STROJIRNA TYC S.R.O	CUSTOMER ORDER REF: 191280 TYC
DISTRIBUTOR:		REDEX ORDER REF: 214625
DESIGNATION:	DRP3+R.31.4.H	SERIAL NUMBER: 904141
CODE:	RX128771-12	MOTOR FLANGE CODE: RX129474-03

Mechanical preload data

The preload torque of the gearbox in DUALDRIVE configuration depends on the application data and features of the gearbox.

The preload torque can be increased but must never exceed the maximum value indicated below.

A too important preload torque reduces the efficiency and the life expectancy of the gearbox and the rack.

Optimal preload torque Tp:	Following application
Maximum preload torque:	36,3 Nm

For the installation, please refer to User Manual DRP (182/009)

SPECIFIC REMARKS:

Product images are for illustrative purposes only.

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

DRP		Page
Performance sheet	RX183/005-B	2/2
EXTERNAL DIMENSIONS & INTERFACES:		SN: 904141
The technical drawing illustrates the external dimensions and interfaces of the RX183/005-B motor. It includes three main views: a top view, a front view, and a side view. The top view shows the motor's footprint with dimensions L1, L2, and E. The front view shows the motor's height and width with dimensions V1, V2, M, and 36 x T. The side view shows the motor's profile with dimensions W, X, H, w, x, and h. Various labels and dimensions are provided for the motor's components and interfaces. Labels and dimensions include: - Top view: 0, J1, J2, J3, 4 x Y on PCD S, ϕB, ϕC, $\phi Q1$, $\phi Q2$. - Front view: V1, V2, M, 36 x T, P11, P12, Q1, Q2, L1, L2, E, G, g, t, u, v, G1, g1, G2, g2. - Side view: W, X, H, w, x, h, Q2, P21, P22.		