

KRPX			Page
Performance sheet		RX183-007-D	1/2
CUSTOMER:	KIHEUNG MACHINERY	CUSTOMER ORDER REF:	W7297-007 KIHEUNG
DISTRIBUTOR:		REDEX ORDER REF:	214861
DESIGNATION:	KRPX2+M.31.3.H.28/38	SERIAL NUMBER:	904240
CODE:	RX131478-12	MOTOR FLANGE CODE:	RX128581-01

For the installation, please refer to User Manual KRPX (182/010)

SPECIFIC REMARKS:

Product images are for illustrative purposes only.

KRPX			Page
Performance sheet		RX183-007-D	2/2
EXTERNAL DIMENSIONS & INTERFACES:		SN:	904240
			

General tolerance: Js13	Cmm	Automatic / manual coordinate-measuring machine	µm	Micrometer	Cr	Calliper rule	Di	Dial indicator	Pg	Plug gauge
-------------------------	-----	--	----	------------	----	---------------	----	----------------	----	------------

HOUSING					HOUSING					MOTOR FLANGE						
requirement			measure		requirement			measure		requirement			measure			
			C1417					L1	60	Cr	60					
	Y2	M6x12	Pg	M6X12		L2	60	Cr	60		Ø	B	181	µm	180,95	
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		J	130	Cr	13		Ø	C	38 ^{+0,05 +0,025}	µm	38,03	
	A	332	µm	332,82		K	11	Cr	11			D	8	Cr	8,49	
	E	240	Cr	240	2 x 4Ø	Y4	M6x12	Pg	M6X12		Ø	S1	215	Cr	215	
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12	
	P1	30	Cr	30		F2	24	Cr	24							
	P2	30	Cr	30	2 x 1Ø	Y7	10	µm	10	No-load input torque						
	P3	30	Cr	30	2 x 4Ø	Y6	15,5	µm	15,5	Line 1				1 Nm		
	P4	30	Cr	30	2 x 5Ø	Y5	24	µm	24							
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10,007				Line	Stiffness		
	U	26	Cr	26	⊥	m	0,05	Cmm	0,02	Torsional stiffness (Nm/arcmin)			1	243,75		
2 x 1Ø	Y3	M6x12	Pg	M6X12		N	55 ^{+0,1 -0,1}	Cmm	55,034							
	R	186 ^{+0,2 +0,1}	Cmm	186,152	A		W	110 ^{+0,02 -0,02}	Cmm	110,02	Radial stiffness (N/µm)			1	647	
◎	r	0,1	Cmm	0,02		//	w	0,03	/A	Cmm						

OUTPUT PINION						Noise level		
					L3770		@1600 rpm input (dB(A))	63,5
Span dimension over 4 teeth								
		G1	44,27 ⁰ _{-0,03}	C _m	44,26			
	↗	g1	0,022	D _i	0,015			

Date: 13/03/2020

Visa: P VASLIER

Version: A