

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	904382
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR						
requerida				real		requerida				real		requerida			real	
				C5936												
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60			B	111	μm	111,09	
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		J	130	Cr	130		Ø	C	24 ^{+0,041 +0,02}	μm	24,03	
	A	312	μm	312,85		K	11	Cr	11			D	8	Cr	8,51	
	E	240	Cr	240	2 x 40	Y4	M6x12	Pg	M6x12		Ø	S1	130	Cr	130	
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M8	Pg	M8	
	P1	30	Cr	30		F2	24	Cr	24	Par entrada sin carga						
	P2	30	Cr	30	2 x 10	Y7	10	μm	10							
	P3	30	Cr	30	2 x 40	Y6	15,5	μm	15,5	Línea 1				0,5 Nm		
	P4	30	Cr	30	2 x 50	Y5	24	μm	24							
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10,003							
	U	26	Cr	26	⊥	m	0,05	Cmm	0,006	Rigidez torsional (Nm/arcmin)		1	243,75			
2 x 10	Y3	M6x12	Pg	M6x12		N	55 ^{+0,1 -0,1}	Cmm	55,01							
	R	186 ^{+0,2 +0,1}	Cmm	186,144	A	W	110 ^{+0,02 -0,02}	Cmm	110,013	Rigidez radial (N/μm)		1	658			
⊙	r	0,1	Cmm	0,011	//	w	0,03	/A	Cmm			0,001				

PIÑÓN DE SALIDA					Nivel sonoro	
			L3731		@1600 rpm entrada (dB(A))	61,0
Medida cordal entre 4 dientes						
		G1	44,27 ⁰ _{-0,03}	Cmm	44,255	
	↗	g1	0,022	Di	0,01	

Revisado: C DE MIRANDA



REDEX

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr

REDEX

ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr