

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	904397
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR						
requerida				real		requerida				real		requerida			real	
				C5937												
Ø	Y2	M6x12	Pg	M6x12		L1	60	Cr	60		Ø	B	181	µm	180,96	
	S2	165 ^{+0,1 -0,1}	Cr	165		L2	60	Cr	60		Ø	C	38 ^{+0,05 +0,025}	µm	38,025	
	A	332	µm	332,75		K	11	Cr	11			D	8	Cr	8,49	
	E	240	Cr	240	2 x 40	Y4	M6x12	Pg	M6x12		Ø	S1	215	Cr	215	
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12	
	P1	30	Cr	30		F2	24	Cr	24	Par entrada sin carga						
	P2	30	Cr	30	2 x 10	Y7	10	µm	10	Línea 1			0,3 Nm			
	P3	30	Cr	30	2 x 40	Y6	15,5	µm	15,5							
	P4	30	Cr	30	2 x 50	Y5	24	µm	24							
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10,003			Línea	Rigidez			
2 x 10	U	26	Cr	26	⊥	m	0,05	Cmm	0,012	Rigidez torsional (Nm/arcmin)		1	243,75			
	Y3	M6x12	Pg	M6x12		N	55 ^{+0,1 -0,1}	Cmm	55,022	Rigidez radial (N/µm)		1	564			
	R	186 ^{+0,2 +0,1}	Cmm	186,145	A	W	110 ^{+0,02 -0,02}	Cmm	110,014							
⊙	r	0,1	Cmm	0,006	//	w	0,03 /A	Cmm	0,002							

PIÑÓN DE SALIDA					Nivel sonoro	
			L3725		@1600 rpm entrada (dB(A))	62,0
Medida cordal entre 4 dientes						
		G1	44,27 ⁰ _{-0,03}	Cmm	44,25	
	↗	q1	0,022	Di	0,01	





ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr



ZI-BP79
F45210 FERRIERES
www.redex.fr

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr