

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	904750
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR							
requerida			real		requerida			real		requerida			real				
			C3832										D416				
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75								
	S2	200 ^{+0,1 -0,1}	Cr	200		L2	70	Cr	70		Ø	B	180 ^{+0,054 +0,014}	µm	180,03		
Ø	V	398	µm	397,48		J	160	Cr	160		Ø	C	38 ^{+0,05 +0,025}	µm	38,05		
	E	290	Cr	290		K	13	Cr	13			D	8	Cr	8,08		
	O	25	Cr	25	2 x 4Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	214,99		
	P1	35	Cr	35		F1	50	Cr	50		Ø	Y1	M12	Pg	M12		
	P2	35	Cr	35	2 x 1Ø	F2	25	Cr	25	Par entrada sin carga							
	P3	35	Cr	35	2 x 4Ø	Y7	12	µm	12							Línea 1	
	P4	35	Cr	35	2 x 5Ø	Y6	17,5	µm	17,5								
	T	17	Cr	17	Y5	26	µm	26	Rígeidez torsional (Nm/arcmin)							1	473,03
	U	32	Cr	32		M H6	12 ^{+0,011 0}	Cmm	12,009	Rígeidez radial (N/µm)					1	1002	
2 x 1Ø	Y3	M8x15	Pg	M8x15		m	0,05	Cmm	0,008								
	R	226 ^{+0,2 +0,1}	Cmm	226,13	A	N	71,5 ^{+0,1 -0,1}	Cmm	71,557								
⊙	r	0,1	Cmm	0,015		W	135 ^{+0,035 -0,035}	Cmm	135,02								
Ø	Q1	30 ^{+0,009 -0,004}	µm	30,005		w	0,03	/A	Cmm	0,006							
Ø	Q2	30 ^{+0,009 -0,004}	µm	30,005	PIÑÓN DE SALIDA					Nivel sonoro							
	J1	/O	Di	-0,03					K141	@1600 rpm entrada (dB(A))					63,0		
					Medida cordal entre 3 dientes												
							G1	39,25 ^{0 -0,03}	Cmm						39,235		
						↗	g1	0,022	Di						0,02		

Fecha: 21/10/2020

Revisado: C DE MIRANDA

Versión: A

	ZI-BP79 F45210 FERRIERES www.redex.fr	Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr		ZI-BP79 F45210 FERRIERES www.redex.fr	Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr
---	---	---	---	---	---