

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 904754



GEHÄUSE					GEHÄUSE					MOTORFLANSCH					
Sollwert			Istwert		Sollwert			Istwert		Sollwert			Istwert		
			C5912					L1	60	Cr	60				
	Y2	M6x12	Pg	M6X12		L2	60	Cr	60		Ø	B	181	µm	180,9
Ø	S2	165 ^{+0,1} _{-0,1}	Cr	164,95		J	130	Cr	130		Ø	C	38 ^{+0,05} _{+0,025}	µm	38,05
	A	295	µm	295,8		K	11	Cr	11			D	8	Cr	8,49
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	M6X12		Ø	S1	215	Cr	215,05
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12
	P1	30	Cr	30		F2	24	Cr	24	Leerlaufdrehmoment					
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10						
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5	Linie 1			2 Nm		
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24						
	T	14	Cr	14		M H6	10 ^{+0,009} ₀	Cmm	10,006						
	U	26	Cr	26	⊥	m	0,05	Cmm	0,013	Verdrehsteifigkeit (Nm/arcmin)			1	243,75	
2 x 1 Ø	Y3	M6x12	Pg	M6X12		N	55 ^{+0,1} _{-0,1}	Cmm	55,02						
	R	186 ^{+0,2} _{+0,1}	Cmm	186,146	A	W	110 ^{+0,02} _{-0,02}	Cmm	110,013	Radiale Steifigkeit (N/µm)			1	554	
⊙	r	0,1	Cmm	0,01	//	w	0,03	/A	Cmm						0,004

ABTRIEBSRITZEL						Geräuschpegel	
	K948				@1100 rpm Eintrieb (dB(A))	55,5	
Zahnweite (über 4 Zähne)							
	G1	44,27 ⁰ _{-0,03}	Cmm	44,255			
	g1	0,022	Di	0,015			

Von: C DE MIRANDA



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex.fr