

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 904769



GEHÄUSE					GEHÄUSE					MOTORFLANSCH				
Sollwert				Istwert	Sollwert				Istwert	Sollwert				Istwert
				B12099		L1	51	Cr	51					
	Y2	M6x12	Pg	M6x12		L2	48	Cr	48	Ø	B	131	µm	130,95
Ø	S2	120 ^{+0,1 -0,1}	Cr	120		J	105	Cr	105	Ø	C	32 ^{+0,05 +0,025}	µm	32,025
	A	253	µm	253,65		K	11	Cr	11		D	8	Cr	8,58
	E	175	Cr	175	2 x 4 Ø	Y4	M6x12	Pg	M6x12	Ø	S1	165	Cr	165
	O	15	Cr	15		F1	40	Cr	40	Ø	Y1	M10	Pg	M10
	P1	24	Cr	24		F2	24	Cr	24	Leerlaufdrehmoment				
	P2	24	Cr	24	2 x 1 Ø	Y7	10	µm	10					
	P3	24	Cr	24	2 x 4 Ø	Y6	11	µm	11	Linie 1				0,2 Nm
	P4	24	Cr	24	2 x 5 Ø	Y5	18	µm	18					
	T	14	Cr	14		M H6	8 ^{+0,009 0}	Cmm	8,007					
	U	26	Cr	26	⊥	m	0,05	Cmm	0,008	Verdrehsteifigkeit (Nm/arcmin)		1	81,39	
2 x 1 Ø	Y3	M6x12	Pg	M6x12		N	47 ^{+0,1 -0,1}	Cmm	47,002					
	R	135 ^{+0,2 +0,1}	Cmm	135,191	A	W	80 ^{+0,02 -0,02}	Cmm	80,012	Radiale Steifigkeit (N/µm)		1	301	
⊙	r	0,1	Cmm	0,016	//	w	0,03 /A	Cmm	0,001					

ABTRIEBSRITZEL						Geräuschpegel	
				L4156		@1600 rpm Eintrieb (dB(A))	62,5
Zahnweite (über 3 Zähne)							
		G1	23,28 ⁰ _{-0,03}	Cmm	23,265		
	↗	g1	0,021	Di	0,005		

Von: P VASLIER

REDEX ZI-BP79 Tel: +33 2 38 94 42 00
F45210 FERRIERES Fax: +33 2 38 94 42 99
www.redex.fr Email: info@redex.fr