

KRP		Page
Scheda di prestazione	RX183-006-A	1/2
CLIENTE:	PAMA	RIF. ORDINE CLIENTE: 609 PAMA
DISTRIBUTORE:	ANDANTEX S.r.l	ORDINE INTERNO: 215438
DESIGNAZIONE:	KRP2+M.31.3.H.28/38	NUMERO DI SERIE: 904778
RIFERIMENTO:	RX128907-12	RIFERIMENTO DELLA FLANGIA MOTORE: RX128581-01

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)

OSSERVAZIONE SPECIFICA:

Le immagini dei prodotti sono a carattere puramente illustrativo.

KRP		Page
Scheda di prestazione	RX183-006-A	2/2
INTERFACCE E DIMENSIONI ESTERNE:		SN: 904778

The drawing illustrates the external dimensions and interfaces of the KRP pump assembly. The main cross-sectional view shows the following dimensions and features:

- Top Flange:** Dimensions include $\varnothing B$ (outer diameter), $\varnothing C$ (inner diameter), and D (thickness). It features **4 x Y on PCD S** (four mounting holes).
- Body:** The main body has a total height of A . It includes a central shaft with a diameter of $\varnothing E1$ and a lower section with a diameter of $\varnothing E2$.
- Mounting Holes:** The lower section has **n x H on PCD J** (n mounting holes with diameter H on a pitch circle diameter J).
- Output Gear:** The bottom view shows a gear with a module of $G1$ and a clearance of $g1$.

General tolerance: Js13				Cmm		Automatic / manual coordinate-measuring machine				µm		Micrometer		Cr		Calliper rule		Di		Dial indicator		Pg		Plug gauge											
CASSA ESTERNA										PIGNONE IN USCITA										FLANGIA DEL MOTORE															
richiesta					misurata					richiesta					misurata					richiesta					misurata										
					C3413										K1835																				
E1					212h7 ⁰ _{-0,046}					µm		211,97			Scostamento (su 4 denti)										Ø		B		181		µm		181		
E2					200h7 ⁰ _{-0,046}					µm		199,98					G1		44,27 ⁰ _{-0,03}		Cmm		44,255			Ø		C		38 ^{+0,05} _{+0,025}		µm		38,05	
n x H on PCD J					12 Ø9 on PCD 233					Cr		12 Ø9 on PCD 233			↗		g1		0,022		Di		0,01					D		8		Cr		8,47	
										Cr													Ø		S1		215		Cr		215				
A					288					µm		288,98			Coppia in ingresso a vuoto										Ø		Y1		M12		Pg		M12		
L					94					µm		93,88			linea 1					0,5 Nm															
																				Livello di rumore															
																				Linea		Rigidità		@1600 rpm entrata (dB(A))		64,0									
																						Rigidità torsionale (Nm/arcmin)		1		243,75									
																						Rigidità radiale (N/µm)		1		580									