

KRP		Page
Scheda di prestazione	RX183-006-A	1/2
CLIENTE:	PAMA	RIF. ORDINE CLIENTE: 765 PAMA
DISTRIBUTORE:	ANDANTEX S.r.l	ORDINE INTERNO: 215575
DESIGNAZIONE:	KRP4+M.61.3.H.35/48	NUMERO DI SERIE: 904957
RIFERIMENTO:	RX128414-32	RIFERIMENTO DELLA FLANGIA MOTORE: RX128583-01

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)

OSSERVAZIONE SPECIFICA:

Le immagini dei prodotti sono a carattere puramente illustrativo.

KRP		Page
Scheda di prestazione	RX183-006-A	2/2
INTERFACCE E DIMENSIONI ESTERNE:		SN: 904957

The drawing illustrates the external dimensions and interfaces of the KRP pump assembly. The main cross-sectional view shows the following features and dimensions:

- Top Flange:** Labeled with $4 \times Y$ on PCD S , indicating four mounting holes. The outer diameter is $\varnothing B$ and the inner diameter is $\varnothing C$. The thickness of the flange is D .
- Body:** The main body has a total height of A . It features a central shaft with a keyway.
- Intermediate Flange:** Labeled with $\varnothing E1$ for the outer diameter and $n \times H$ on PCD J for the mounting holes. The inner diameter is $\varnothing E2$.
- Bottom Flange:** Labeled with $\varnothing E2$ for the inner diameter. The distance from the bottom of the main body to the bottom of this flange is L .
- Output Gear:** A side view of the output gear is shown at the bottom, with a pitch diameter of $G1$ and a clearance of $g1$.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge	
CASSA ESTERNA						PIGNONE IN USCITA						FLANGIA DEL MOTORE					
richiesta				misurata		richiesta				misurata		richiesta				misurata	
				D3131						K1862							
		E1	285h7 ⁰ _{-0,052}	µm	284,97	Scostamento (su 3 denti)						Ø	B	181	µm	181	
		E2	285h7 ⁰ _{-0,052}	µm	284,98		G1	46,9 ⁰ _{-0,03}	Cmm	46,88	Ø	C	38 ^{+0,05} _{+0,025}	µm	38,03		
n x H on PCD J		16 Ø14 on PCD 310	Cr	16 Ø14 on PCD 310	↗	g1	0,022	Di	0,02		D	8	Cr	8,47			
			Cr							Ø	S1	215	Cr	215			
		A	373,5	µm	374,15	Coppia in ingresso a vuoto						Ø	Y1	M12	Pg	M12	
		L	141	µm	141,44	linea 1				0,5 Nm							
												Livello di rumore					
								Linea	Rigidità		@1300 rpm entrata (dB(A))				63,0		
						Rigidità torsionale (Nm/arcmin)		1	574,81								
						Rigidità radiale (N/µm)		1	1238								

Date: 04/02/2021

Visa: C DE MIRANDA

Version: A