

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	905286
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR																
requerida					real		requerida					real		requerida					real							
					C5930																					
Y2					M6x12	Pg	M6x12	L1					60	Cr	60											
Ø					S2	165 ^{+0,1 -0,1}	Cr	165	L2					60	Cr	60	Ø					B	181	µm	180,95	
					A	332	µm	332,63	J					130	Cr	130	Ø					C	38 ^{+0,05 +0,025}	µm	38,05	
					E	240	Cr	240	K					11	Cr	11						D	8	Cr	8,45	
					O	15	Cr	15	2 x 4 Ø					Y4	M6x12	Pg	M6x12	Ø					S1	215	Cr	215
					P1	30	Cr	30						F1	40	Cr	40	Ø					Y1	M12	Pg	M12
					P2	30	Cr	30						F2	24	Cr	24	Par entrada sin carga								
					P3	30	Cr	30	2 x 1 Ø					Y7	10	µm	10									
					P4	30	Cr	30	2 x 4 Ø					Y6	15,5	µm	15,5	Línea 1					1 Nm			
					T	14	Cr	14	2 x 5 Ø					Y5	24	µm	24									
					U	26	Cr	26						M H6	10 ^{+0,009 0}	Cmm	10,002	Rígedez torsional (Nm/arcmin)			1	243,75				
2 x 1 Ø					Y3	M6x12	Pg	M6x12						m	0,05	Cmm	0,005									
					R	186 ^{+0,2 +0,1}	Cmm	186,151	A						N	55 ^{+0,1 -0,1}	Cmm	54,979	Rígedez radial (N/µm)			1	550			
⊙					r	0,1	Cmm	0,038	//					w	0,03	/A	Cmm	0,001								

PIÑÓN DE SALIDA						Nivel sonoro	
	J121				@1600 rpm entrada (dB(A))	66,0	
Medida cordal entre 4 dientes							
	G1	44,27 ⁰ _{-0,03}	Cmm	44,25			
	g1	0,022	Di	0,02			



		ZI-BP79 F45210 FERRIERES www.redex.fr	Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr			ZI-BP79 F45210 FERRIERES www.redex.fr	Tel: +33 2 38 94 42 00 Fax: +33 2 38 94 42 99 Email: info@redex.fr
---	--	---	---	---	--	---	---